



Generator Documentation

Release 3.7

/ELSA/MU-09022/V3.7

Oct 19, 2023

CONTENTS

1	Preamble	1
2	List of functions	3
3	Contents	9
3.1	Basic grid generation	9
3.2	General purpose grid generator	19
3.3	Cartesian grid generators	43
3.4	Operations on meshes	51
3.5	Operation on surface meshes	69
3.6	Information on generated meshes	74
3.7	Operations on distributions	94
4	Index	103

PREAMBLE

Generator module works on arrays (as defined in Converter) or on CGNS/python trees (pyTrees) containing grid information (coordinates must be defined).

This module is part of Cassiopee, a free open-source pre- and post-processor for CFD simulations.

For use with the array interface, you have to import Generator module:

```
import Generator as G
```

For use with the pyTree interface:

```
import Generator.PyTree as G
```


LIST OF FUNCTIONS

– Basic grid generation

<code>Generator.cart(Xo, H, N[, api])</code>	Create a cartesian mesh defined by a structured array.
<code>Generator.cartr1(Xo, H, R, N[, doubleLeft, ...])</code>	Create a structured cartesian mesh with geometric distribution.
<code>Generator.cartr2(Xo, H, R, Xf[, doubleLeft, ...])</code>	Create a structured cartesian mesh with geometric distribution fixing last point.
<code>Generator.cartHexa(Xo, H, N[, api])</code>	Create a cartesian mesh defined by an hexaedrical array.
<code>Generator.cartTetra(Xo, H, N[, api])</code>	Create a cartesian mesh defined by a tetraedrical array.
<code>Generator.cartPenta(Xo, H, N[, api])</code>	Create a cartesian mesh defined by a prismatic array.
<code>Generator.cartPyra(Xo, H, N[, api])</code>	Create a cartesian mesh defined by a pyramidal array.
<code>Generator.cartNGon(Xo, H, N[, api])</code>	Create a cartesian mesh defined by a NGON array.
<code>Generator.cylinder(Xo, R1, R2, tetas, tetae, ...)</code>	Create a portion of regular cylindrical grid.
<code>Generator.cylinder2(Xo, R1, R2, tetas, ...)</code>	Create a portion of cylindrical grid.
<code>Generator.cylinder3(arrayxz, tetas, tetae, ...)</code>	Create a portion of cylindrical grid.

– General purpose grid generators

<code>Generator.delaunay(array[, tol, keepBB])</code>	Create a delaunay mesh given a set of points defined by array.
<code>Generator.constrainedDelaunay(cont0[, tol, ...])</code>	Create a constrained-Delaunay mesh starting from a BAR-array defining the contour.
<code>Generator.checkDelaunay(contour, tri)</code>	Check if the Delaunay triangulation defined by tri is inside the contour.
<code>Generator.T3mesher2D(a[, grading, ...])</code>	Create a delaunay mesh given a set of points defined by a.
<code>Generator.tetraMesher(a[, maxh, grading, ...])</code>	Create a TRI/TETRA mesh given a set of BAR or surfaces in a.
<code>Generator.TFI(arrays)</code>	Generate a transfinite interpolation mesh from boundaries.
<code>Generator.TFITri(a1, a2, a3)</code>	Generate a transfinite interpolation mesh from 3 input curves.
<code>Generator.TFI0(a[, weight])</code>	Generate a transfinite interpolation mesh for 1 input curve.
<code>Generator.TFIHalf0(a1, a2)</code>	Generate a transfinite interpolation mesh for 2 input curves.
<code>Generator.TFIMono(a1, a2)</code>	Generate a transfinite interpolation mesh for 2 input curves.
<code>Generator.TFIStar(a)</code>	Generate a transfinite interpolation mesh for a list of input curves.
<code>Generator.hyper2D(array, arrayd, type[, ...])</code>	Generate an hyperbolic mesh.
<code>Generator.PolyLine.polyLineMesher(polyLine, ...)</code>	Generate a multiple mesh for a polyline.
<code>Generator.PolyC1.polyC1Mesher(curve, h, ...)</code>	Generate a multiple mesh for a C1 curve (polyC1).
<code>Generator.pointedHat(array, coord)</code>	Create a structured surface defined by a contour and a point (x,y,z).
<code>Generator.stitchedHat(array, offset[, tol, tol2])</code>	Create a structured surface defined by a contour and an offset (dx,dy,dz).
<code>Generator.surfaceWalk(surfaces, c, distrib)</code>	Generate a surface mesh by a walk on a list of surfaces, starting from a contour c and following constraints.
<code>Generator.collarMesh(s1, s2, distribj, distribk)</code>	Generates a collar mesh starting from s1 and s2 surfaces, distributions along the surfaces and along the normal direction, with respect to the assembly type between grids.

– Cartesian grid generators

<code>Generator.gencartmb(bodies, h, Dfar, nlvl)</code>	Generate a multiblock Cartesian mesh.
<code>Generator.octree(stlArrays[, snearList, ...])</code>	Generate an octree (or a quadtree) mesh starting from a list of TRI (or BAR) arrays defining bodies, a list of corresponding snears, and the extension dfar of the mesh.
<code>Generator.octree2Struct(a[, vmin, ext, ...])</code>	Generates a structured set of regular Cartesian grid starting from an octree HEXA or QUAD mesh.
<code>Generator.adaptOctree(octreeHexa, indicField)</code>	Adapt an unstructured octree w.r.t.
<code>Generator.expandLayer(octreeHexa[, level, ...])</code>	Expand the layer of octree elements of level l of one additional layer.
<code>Generator.PyTree.cartRx(X0, H, N, Nb[, ...])</code>	Create a set of regular cartesian grids.
<code>Generator.PyTree.cartRx3(XC0, XC1, HC, XF0, ...)</code>	Create a set of regular and geometric cartesian grids with double steps.

– Operations on meshes

<code>Generator.close(array[, tol, ...])</code>	Close a mesh defined by an array gathering points closer than tol.
<code>Generator.selectInsideElts(array, curvesList)</code>	Select elements whose center is in the surface delimited by curves.
<code>Generator.map(array, d[, dir, h1, h2, ...])</code>	Map a distribution on a curve or a surface.
<code>Generator.mapSplit(array, dist[, splitCrit, ...])</code>	Split a curve and map a distribution on the set of split curves.
<code>Generator.refine(array, power[, dir])</code>	Refine a mesh of power power along all the directions or on a specified one.
<code>Generator.mapCurvature(array, N, power, dir)</code>	Remesh with a step proportional to curvature.
<code>Generator.densify(array, h)</code>	Densify a mesh.
<code>Generator.grow(array, vector)</code>	Grow a surface array of one layer by displacing points of vector.
<code>Generator.stack(array1[, array2])</code>	Stack two meshes (with same nixnj) into a single mesh.
<code>Generator.addNormalLayers(surface, distrib)</code>	Generate N layers to a surface following normals.
<code>Generator.TTM(array[, niter])</code>	Smooth a mesh with Thompson-Mastin elliptic generator.
<code>Generator.snapFront(meshes, surfaces[, ...])</code>	Adapt meshes to a given surface (cellN defined).
<code>Generator.snapSharpEdges(meshes, surfaces[, ...])</code>	Adapt meshes to a given surface sharp edges.

– Operations on surface meshes

<code>Generator.fittingPlaster(contour[, bumpFactor])</code>	Generate a structured points cloud over a BAR.
<code>Generator.gapfixer(contour, cloud[, ...])</code>	Fix a gap defined by a contour bar and a point cloud representing the gap surface.
<code>Generator.gapsmanager(components[, mode, ...])</code>	Fix a gap between several component surfaces (list of arrays).
<code>Generator.mmgs(array[, ridgeAngle, hmin, ...])</code>	Surface remeshing using MMGS.

– Information on generated meshes

<code>Generator.barycenter(array[, weight])</code>	Get the barycenter of an array.
<code>Generator.bbox(arrays)</code>	Returns the bounding box of a list of arrays.
<code>Generator.bboxOfCells(array)</code>	Return the bounding box of all cells of an array.
<code>Generator.BB(array[, method, weighting, tol])</code>	Return the axis-aligned or oriented bounding box of an array as an array.
<code>Generator.CEBBIntersection(array1, array2[, tol])</code>	Get the Cartesian Elements bounding box intersection of 2 arrays.
<code>Generator.bboxIntersection(array1, array2[, ...])</code>	Return the intersection of bounding boxes of 2 arrays.
<code>Generator.checkPointInCEBB(array, P)</code>	Check if point P is in the Cartesian Elements Bounding Box of array.
<code>Generator.getVolumeMap(array)</code>	Return the volume map in an array.
<code>Generator.getNormalMap(array)</code>	Return the map of surface normals in an array.
<code>Generator.getSmoothNormalMap(array[, niter, ...])</code>	Return the map of smoothed surface normals in an array.
<code>Generator.getOrthogonalityMap(array)</code>	Return the orthogonality map in an array.
<code>Generator.getRegularityMap(array)</code>	Return the regularity map in an array.
<code>Generator.getAngleRegularityMap(array)</code>	Return the regularity map in an array.
<code>Generator.getTriQualityMap(array)</code>	Return a TRI quality measure map in an array.
<code>Generator.getCellPlanarity(array)</code>	Return the cell planarity of a surface mesh in an array.
<code>Generator.getCircumCircleMap(array)</code>	Return the map of circum circle radius of any cell in a TRI array.
<code>Generator.getInCircleMap(array)</code>	Return the map of inscribed circle radius of any cell in a TRI array.
<code>Generator.getEdgeRatio(array[, dim])</code>	Computes the ratio between the max and min lengths of all the edges of cells in an array.
<code>Generator.getMaxLength(array[, dim])</code>	Computes the max length of all the edges of cells in an array.
<code>Generator.checkMesh(array[, critVol, ...])</code>	Return information on mesh quality.

– Operations on distributions

<code>Generator.enforceX(array, x0, enforcedh, N)</code>		Enforce a x_0 -centered line in a distribution defined by an array.
<code>Generator.enforceMoinsX(array, enforcedh, N)</code>	en-	Enforce the last X-line in a distribution (one sided, left).
<code>Generator.enforcePlusX(array, enforcedh, N)</code>	en-	Enforce the first X-line in a distribution defined by an array.
<code>Generator.enforceLine(array, arrayline, ...)</code>		Enforce a line in a distribution.
<code>Generator.enforcePoint(array, x0)</code>		Enforce a point in a distribution.
<code>Generator.enforceCurvature(arrayD, arrayC[, ...])</code>	ar-	Enforce curvature of a curve in a distribution.
<code>Generator.addPointInDistribution(array, ind)</code>		Add a point in a distribution defined by array.

CONTENTS

3.1 Basic grid generation

Generator.**cart**((*xo, yo, zo*), (*hi, hj, hk*), (*ni, nj, nk*))

Create a structured Cartesian mesh with *ni* x *nj* x *nk* points starting from point (*xo,yo,zo*) and of step (*hi,hj,hk*).

Parameters

- (**xo,yo,zo**) (3-tuple of floats) – coordinates of the starting point
- (**hi,hj,hk**) (3-tuple of floats) – values of advancing step in the three directions
- (**ni,nj,nk**) (3-tuple of integers) – number of points in each direction

Returns

a 1D, 2D or 3D structured mesh

Return type

array or pyTree zone

Example of use:

- Cartesian mesh generation (array):

```
# - cart (array) -
import Converter as C
import Generator as G
a = G.cart((0.,0.,0.), (0.1,0.1,0.2), (10,10,10))
C.convertArrays2File(a, 'out.plt')
```

- Cartesian mesh generation (pyTree):

```
# - cart (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G

a = G.cart((0.,0.,0.), (0.1,0.1,0.2), (10,11,12))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**cartr1**((*xo, yo, zo*), (*hi, hj, hk*), (*ri, rj, rk*), (*ni, nj, nk*))

Create a structured Cartesian mesh with geometric distribution of factors r. (*hi,hj,hk*) are the steps of first cell.

Parameters

- (**xo,yo,zo**) (3-tuple of floats) – coordinates of the starting point
- (**hi,hj,hk**) (3-tuple of floats) – Step of first cell in the three directions
- (**ri,rj,rk**) (3-tuple of floats) – geometric factors in the three directions
- (**ni,nj,nk**) (3-tuple of integers) – number of points in each direction

Returns

a 1D, 2D or 3D structured mesh

Return type

array or pyTree zone

Example of use:

- Geometric Cartesian mesh generation (array):

```
# - cartr1 (array) -
import Generator as G
import Converter as C

a = G.cartr1((0,0,0), (1.,1.,1.), (1.1,1.2,1.), (10,10,10))
C.convertArrays2File(a, 'out.plt')
```

- Geometric Cartesian mesh generation (pyTree):

```
# - cartr1 (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
```

(continues on next page)

(continued from previous page)

```
a = G.cartr1((0,0,0), (1.,1.,1.), (1.1,1.2,1.), (10,10,10))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**cartr2**((*xo, yo, zo*), (*hi, hj, hk*), (*ri, rj, rk*), (*xf, yf, zf*))

Create a structured Cartesian mesh with geometric distribution of factors *r*. (*hi,hj,hk*) are the steps of first cell. (*xf,yf,zf*) are coordinates of last point. (*hi,hj,hk*) or (*ri,rj,rk*) can be slightly modified to match (*xf,yf,zf*).

Parameters

- (**xo,yo,zo**) (3-tuple of floats) – coordinates of the starting point
- (**hi,hj,hk**) (3-tuple of floats) – Step of first cell in the three directions
- (**ri,rj,rk**) (3-tuple of floats) – geometric factors in the three directions
- (**ni,nj,nk**) (3-tuple of integers) – number of points in each direction

Returns

a 1D, 2D or 3D structured mesh

Return type

array or pyTree zone

Example of use:

- Geometric Cartesian mesh with fixed last point (array):

```
# - cartr2 (array) -
import Generator as G
import Converter as C

a = G.cartr2((10,5,1), (1,1,1), (1.5,1.3,1.), (200.,100.,100.))
C.convertArrays2File(a, 'out.plt')
```

- Geometric Cartesian mesh with fixed last point (pyTree):

```
# - cartr2 (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
```

(continues on next page)

(continued from previous page)

```
a = G.cartr2((10,5,1), (1,1,1), (1.5,1.3,1.), (200.,100.,100.))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**cartHexa**((*xo, yo, zo*), (*hi, hj, hk*), (*ni, nj, nk*))

Create an unstructured hexahedral mesh defined from a Cartesian grid of $n_i \times n_j \times n_k$ points starting from point (*xo,yo,zo*) and of step (*hi,hj,hk*). Type of elements are 'QUAD' for 2D arrays and 'HEXA' for 3D arrays.

Parameters

- (**xo, yo, zo**) (3-tuple of floats) – coordinates of the starting point
- (**hi, hj, hk**) (3-tuple of floats) – values of advancing step in the three directions
- (**ni, nj, nk**) (3-tuple of integers) – number of points in each direction

Returns

a 1D, 2D or 3D unstructured mesh

Return type

array or pyTree zone

Example of use:

- Cartesian hexa mesh generation (array):

```
# - cartHexa (array) -
import Generator as G
import Converter as C

a = G.cartHexa((0.,0.,0.), (0.1,0.1,0.2), (10,10,10))
C.convertArrays2File([a], 'out.plt')
```

- Cartesian hexa mesh generation (pyTree):

```
# - cartHexa (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cartHexa((0.,0.,0.), (0.1,0.1,0.2), (10,10,1))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**cartTetra**((*xo, yo, zo*), (*hi, hj, hk*), (*ni, nj, nk*))

Create an unstructured tetrahedral mesh defined from a Cartesian grid of $n_i \times n_j \times n_k$ points starting from point (*xo,yo,zo*) and of step (*hi,hj,hk*). Type of elements are 'TRI' for 2D arrays and 'TETRA' for 3D arrays.

Parameters

- (**xo,yo,zo**) (3-tuple of floats) – coordinates of the starting point
- (**hi,hj,hk**) (3-tuple of floats) – values of advancing step in the three directions
- (**ni,nj,nk**) (3-tuple of integers) – number of points in each direction

Returns

a 1D, 2D or 3D unstructured mesh

Return type

array or pyTree zone

Example of use:

- Cartesian tetra mesh generation (array):

```
# - cartTetra (array) -
import Generator as G
import Converter as C
a = G.cartTetra((0.,0.,0.), (0.1,0.1,0.2), (10,10,1))
C.convertArrays2File(a, 'out.plt')
```

- Cartesian tetra mesh generation (pyTree):

```
# - cartTetra (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cartTetra((0.,0.,0.), (0.1,0.1,0.2), (10,10,1))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**cartPenta**((*xo, yo, zo*), (*hi, hj, hk*), (*ni, nj, nk*))

Create an unstructured prismatic mesh defined from a regular Cartesian mesh. The initial Cartesian mesh is defined by $n_i \times n_j \times n_k$ points starting from point (*xo,yo,zo*) and of step (*hi,hj,hk*). Type of elements is 'PENTA'.

Parameters

- (**xo,yo,zo**) (3-tuple of floats) – coordinates of the starting point

- **(hi,hj,hk)** (3-tuple of floats) – values of advancing step in the three directions
- **(ni,nj,nk)** (3-tuple of integers) – number of points in each direction

Returns

a 1D, 2D or 3D unstructured mesh

Return type

array or pyTree zone

Example of use:

- Cartesian penta mesh generation (array):

```
# - cartPenta (array) -
import Generator as G
import Converter as C
a = G.cartPenta((0.,0.,0.), (0.1,0.1,0.2), (10,10,10))
C.convertArrays2File([a], "out.plt")
```

- Cartesian penta mesh generation (pyTree):

```
# - cartPenta (pyTree)-
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cartPenta((0.,0.,0.), (0.1,0.1,0.2), (10,10,10))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**cartPyra**((xo, yo, zo), (hi, hj, hk), (ni, nj, nk))

Create an unstructured pyramidal mesh defined from a regular Cartesian mesh. The initial Cartesian mesh is defined by ni x nj x nk points starting from point (xo,yo,zo) and of step (hi,hj,hk). Type of elements is 'PYRA'.

Parameters

- **(xo,yo,zo)** (3-tuple of floats) – coordinates of the starting point
- **(hi,hj,hk)** (3-tuple of floats) – values of advancing step in the three directions
- **(ni,nj,nk)** (3-tuple of integers) – number of points in each direction

Returns

a 1D, 2D or 3D unstructured mesh

Return type

array or pyTree zone

Example of use:

- Cartesian pyra mesh generation (array):

```
# - cartHexa (array) -
import Generator as G
import Converter as C

a = G.cartPyra((0.,0.,0.), (1,1,1), (20,20,20))
C.convertArrays2File(a, 'out.tp')
```

- Cartesian pyra mesh generation (pyTree):

```
# - cartPyra (pyTree)-
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cartPyra((0.,0.,0.), (0.1,0.1,0.2), (10,10,10))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**cartNGon**((*xo, yo, zo*), (*hi, hj, hk*), (*ni, nj, nk*))

Create a NGON mesh defined from a regular Cartesian mesh. The initial Cartesian mesh is defined by $n_i \times n_j \times n_k$ points starting from point (*xo,yo,zo*) and of step (*hi,hj,hk*). Type of elements is 'NGON'.

Parameters

- (**xo,yo,zo**) (3-tuple of floats) – coordinates of the starting point
- (**hi,hj,hk**) (3-tuple of floats) – values of advancing step in the three directions
- (**ni,nj,nk**) (3-tuple of integers) – number of points in each direction

Returns

a 1D, 2D or 3D unstructured mesh

Return type

array or pyTree zone

Example of use:

- Cartesian ngon mesh generation (array):

```
# - cartNGon (array) -
import Generator as G
import Converter as C

a = G.cartNGon((0.,0.,0.), (0.1,0.1,0.2), (20,20,20))
C.convertArrays2File(a, 'out.plt')
```

- Cartesian ngon mesh generation (pyTree):

```
# - cartNGon (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cartNGon((0.,0.,0.), (0.1,0.1,0.2), (2,2,2))
C.convertPyTree2File(a, 'out.cgns')
```

`Generator.cylinder((xo, yo, zo), R1, R2, tetas, tetae, H, (ni, nj, nk))`

Create a regular cylindrical grid (or a portion of cylinder between tetas and tetae) with ni x nj x nk points, of center-bottom point (xo,yo,zo), of inner radius R1, outer radius R2 and height H. For a direct mesh, use tetae < tetas.

Parameters

- **(xo,yo,zo)** (3-tuple of floats) – coordinates of the starting point
- **R1** (float) – value of inner radius
- **R2** (float) – value of outer radius
- **tetas** (float) – start angle (in degree)
- **tetae** (float) – end angle (in degree)
- **(ni,nj,nk)** (3-tuple of integers) – number of points in each direction

Returns

a 3D structured mesh

Return type

array or pyTree zone

Example of use:

- Regular cylinder mesh generation (array):

```
# - cylinder (array) -
import Generator as G
import Converter as C
a = G.cylinder((0.,0.,0.), 0.5, 1., 360., 0., 10., (50,50,30))
C.convertArrays2File([a], "out.plt")
```

- Regular cylinder mesh generation (pyTree):

```
# - cylinder (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
a = G.cylinder((0.,0.,0.), 0.5, 1., 360., 0., 10., (50,50,30))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**cylinder2**((*xo, yo, zo*), *R1*, *R2*, *tetas*, *tetae*, *H*, *arrayR*, *arrayTeta*, *arrayZ*)

Create an irregular cylindrical grid (or a portion of cylinder between *tetas* and *tetae*) with $n_i \times n_j \times n_k$ points, of center-bottom point (*xo,yo,zo*), of inner radius *R1*, outer radius *R2*, height *H* and with distributions in *r*, *teta*, *z*. Distributions are arrays defining 1D meshes (*x* and *i* varying) giving a distribution in [0,1]. Their number of points gives n_i , n_j , n_k .

Parameters

- (**xo,yo,zo**) (3-tuple of floats) – coordinates of the starting point
- **R1** (float) – value of inner radius
- **R2** (float) – value of outer radius
- **tetas** (float) – start angle (in degree)
- **tetae** (float) – end angle (in degree)
- **H** (float) – value of cylinder height
- **arrayR** (array) – distribution along radius
- **arrayTeta** (array) – distribution along azimuth
- **arrayZ** (array) – distribution along height

Returns

a 3D structured mesh

Return type

array or pyTree zone

Example of use:

- Irregular cylinder mesh generation (array):

```
# - cylinder2 (array) -
import Converter as C
import Generator as G
r = G.cart((0.,0.,0.), (0.1, 1., 1.), (11, 1, 1))
teta = G.cart((0.,0.,0.), (0.1, 1., 1.), (11, 1, 1))
z = G.cart((0.,0.,0.), (0.1, 1., 1.), (11, 1, 1))
cyl = G.cylinder2( (0.,0.,0.), 0.5, 1., 360., 0., 10., r, teta, z)
C.convertArrays2File([cyl], "out.plt")
```

- Irregular cylinder mesh generation (pyTree):

```
# - cylinder2 (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G

r = G.cart((0.,0.,0.), (0.1, 1., 1.), (11, 1, 1))
teta = G.cart((0.,0.,0.), (0.1, 1., 1.), (11, 1, 1))
z = G.cart((0.,0.,0.), (0.1, 1., 1.), (11, 1, 1))

cyl = G.cylinder2( (0.,0.,0.), 0.5, 1., 360., 0., 10., r, teta, z)
C.convertPyTree2File(cyl, 'out.cgns')
```

Generator.**cylinder3**(*a*, *tetas*, *tetae*, *arrayTeta*)

Create an irregular cylindrical grid (or a portion of cylinder between *tetas* and *tetae*) from a *xz* plane mesh defined by *a* and a *teta* distribution defined by *arrayTeta*.

Parameters

- **a** ([array, list of arrays] or [zone, list of zones, base, pyTree]) – definition of the *xz* plane mesh
- **tetas** (float) – start angle (in degree)
- **tetae** (float) – end angle (in degree)
- **arrayTeta** (array) – distribution along azimuth

Returns

a 3D structured mesh

Return type

array or pyTree zone

Example of use:

- Irregular cylinder mesh generation from a xz plane (array):

```
# - cylinder3 (array) -
import Generator as G
import Converter as C
teta = G.cart((0.,0.,0.), (0.1, 1., 1.), (11, 1, 1))
xz = G.cart((0.1,0.,0.), (0.1,1.,0.2), (20, 1, 30))
cyl = G.cylinder3( xz, 0., 90., teta)
C.convertArrays2File([cyl], 'out.plt')
```

- Irregular cylinder mesh generation from a xz plane (pyTree):

```
# - cylinder3 (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
teta = G.cart((0.,0.,0.), (0.1, 1., 1.), (11, 1, 1))
xz = G.cart((0.1,0.,0.), (0.1,1.,0.2), (20, 1, 30))
cyl = G.cylinder3(xz, 0., 90., teta)
C.convertPyTree2File(cyl, 'out.cgns')
```

3.2 General purpose grid generator

Generator.**del**aunay(*a*, *tol*=1.e-10, *keepBB*=0)

Create a 2D Delaunay type mesh from an array. The array can be a 2D structured array, or an unstructured array of type 'NODE', 'TRI' or 'QUAD'. Tol is a geometric tolerance. Points nearer than tol are merged. If keepBB is set to 1, the bounding box is kept in the final triangulation.

Parameters

- **a** ([array] or [zone]) – structured or unstructured 2D mesh
- **tol** (float) – geometric tolerance
- **keepBB** (integer (0 or 1)) – keep bounding box in result?

Returns

a 2D unstructured mesh

Return type

Identical to a

Example of use:

- 2D Delaunay mesh generation (array):

```
# - delaunay (array) -
import Generator as G
import Converter as C
ni = 11; nj = 11; nk = 1
hi = 1./(ni-1); hj = 1./(nj-1); hk = 1.
a = G.cart((0.,0.,0.), (hi,hj,hk), (ni,nj,nk))
b = G.delaunay(a)
C.convertArrays2File([a,b], "out.plt")
```

- 2D Delaunay mesh generation (pyTree):

```
# - delaunay (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G

ni = 11; nj = 11; nk = 1
hi = 1./(ni-1); hj = 1./(nj-1); hk = 1.
a = G.cart((0.,0.,0.), (hi,hj,hk), (ni,nj,nk))
b = G.delaunay(a); b[0] = 'delaunay'
t = C.newPyTree(['Base', 2, a,b])
C.convertPyTree2File(t, 'out.cgns')
```

Generator.**constrainedDelaunay**(*c*, *tol*=1.e-10, *keepBB*=0)

Create a constrained Delaunay triangulation of the convex hull of a contour *c*. Contour must be a BAR-array and must be in the plane (x,y). Tol is a geometric tolerance. Points nearer than tol are merged. If keepBB is set to 1, the bounding box is kept in the final triangulation.

Parameters

- **c** (BAR-array) – contour in xy plane
- **tol** (float) – geometric tolerance
- **keepBB** (integer (0 or 1)) – keep bounding box in result?

Returns

a 2D unstructured mesh

Return type

Identical to a

Example of use:

- 2D Delaunay mesh generation from a contour (array):


```
# - constrainedDelaunay (array) -
import Converter as C
import Generator as G
import Transform as T
import Geom as D

A = D.text1D('CASSIOPEE')
A = C.convertArray2Tetra(A); a = T.join(A)
# Triangulation respecting given contour
tri = G.constrainedDelaunay(a)
C.convertArrays2File([a,tri], "out.plt")
```

- 2D Delaunay mesh generation from a contour (pyTree):

```
# - constrainedDelaunay (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D
import Transform.PyTree as T

A = D.text1D('CASSIOPEE')
A = C.convertArray2Tetra(A); a = T.join(A)
# Triangulation respecting given contour
tri = G.constrainedDelaunay(a)
C.convertPyTree2File(tri, 'out.cgns')
```

Generator.**checkDelaunay**(*c*, *tri*)

Check if the Delaunay triangulation defined in *tri* is inside the contour *c*.

Parameters

- **c** (BAR-array) – contour in xy plane
- **tri** (array or pyTree) – 2D Delaunay triangulation mesh

Returns

contour

Return type

BAR-array

Example of use:

- Check Delaunay triangulation wrt. contour (array):

```
# - checkDelaunay (array) -
import Converter as C
import Generator as G
import Transform as T
import Geom as D

A = D.text1D('CASSIOPEE')
A = C.convertArray2Tetra(A); a = T.join(A)
# Triangulation respecting given contour
tri = G.constrainedDelaunay(a)
res = G.checkDelaunay(a, tri)
C.convertArrays2File([res], "out.plt")
```

- Check Delaunay triangulation wrt. contour (pyTree):

```
# - checkDelaunay (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D
import Transform.PyTree as T

A = D.text1D('CASSIOPEE')
A = C.convertArray2Tetra(A); a = T.join(A)
# Triangulation respecting given contour
tri = G.constrainedDelaunay(a)
res = G.checkDelaunay(a, tri)
C.convertPyTree2File(res, "out.cgns")
```

Generator.**T3mesher2D**(*a*, *triangulateOnly*=0, *grading*=1.2, *metricInterpType*=0)

Creates a 2D Delaunay mesh given a BAR defined in *a*. If *triangulateOnly*=1 then only points of *a* are triangulated, if *triangulateOnly*=0, then interior points are inserted.

The *grading* parameter allows to control the growth ratio of the mesh metric : a value greater(lesser) than 1. tends to produce a coarser (finer) mesh in the region far from the boundaries. A value equal to 1. provides a uniform mesh over the domain. This *grading* is related to the metric field, it is not the size ratio between two adjacent edges or triangles.

The *metricInterpType* parameter controls the metrics interpolation type: either linear or geometric. A geometric metric interpolation tends to promote smaller sizes.

Parameters

- **c** ([array, list of arrays] or [pyTree, base, zone, list of zones]) – BAR-contour (soup of conformal edges defining an enclosed 2D-domain, can be non-manifold, i.e. having inner edges or subdomains)
- **triangulateOnly** (integer (0 or 1)) – insertion or not of interior points for the triangulation
- **grading** (float (strictly positive value)) – metric growth ratio
- **metricInterpType** (integer (0 or 1)) – metric interpolation type, linear(0) or geometric(1)

Returns

2D mesh

Return type

Identical to input

Example of use:

- 2D Delaunay mesh generation from a BAR (array):

```
# - T3mesher2D (array) -
import Generator as G
import Converter as C
import Geom as D

a = D.circle((0,0,0), 1, N=50)
a = C.convertArray2Tetra(a)
a = G.close(a)
b = G.T3mesher2D(a, triangulateOnly=0, grading=1.2, metricInterpType=0)
↪# linear metric interpolation
C.convertArrays2File([a,b], 'outL.plt')

b = G.T3mesher2D(a, triangulateOnly=0, grading=1.2, metricInterpType=1)
↪# geometric metric interpolation
C.convertArrays2File([a,b], 'outG.plt')
```

- 2D Delaunay mesh generation from a BAR (pyTree):

```
# - T3mesher2D (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

a = D.circle((0,0,0), 1, N=50)
```

(continues on next page)

(continued from previous page)

```

a = C.convertArray2Tetra(a)
a = G.close(a)

b = G.T3mesher2D(a, triangulateOnly=0, grading=1.2, metricInterpType=0)
↪# linear metric interpolation
C.convertPyTree2File(b, 'outL.cgns')

b = G.T3mesher2D(a, triangulateOnly=0, grading=1.2, metricInterpType=1)
↪# geometric metric interpolation
C.convertPyTree2File(b, 'outG.cgns')

```

Generator.**tetraMesher**(*a*, *maxh*=-1., *grading*=0.4, *algo*=1, *optionString*="")

Create a 3D tetra mesh given a TRI surface defined in *a*. If the TRI surface has external normals, tetras are filled inside the surface. If *algo*=0, netgen is used, if *algo*=1, tetgen is used.

Parameters

- **c** ([array, list of arrays] or [zone, list of zones, base, pyTree]) – triangulated surface mesh
- **maxh** (float) – max cell size of generated mesh [tetgen]
- **grading** (float) – max adjacent cell ratio [tetgen]
- **optionString** (string) – string of options identical to tetgen [tetgen]
- **algo** (integer (0 or 1)) – choice parameter between netgen and tetgen

Returns

3D mesh

Return type

[array] or [pyTree zone]

Example of use:

- 3D tetra mesh generation (array):

```

# - tetraMesher (array) -
import Generator as G
import Converter as C
import Post as P
import Transform as T

```

(continues on next page)

(continued from previous page)

```

a = G.cart((0,0,0), (1,1,1), (3,3,3))
ext = P.exteriorFaces(a)
ext = C.convertArray2Tetra(ext)
ext = G.close(ext)
ext = T.reorder(ext, (-1,))
m = G.tetraMesher(ext, algo=1)
C.convertArrays2File(m, 'out.plt')

```

- 3D tetra mesh generation (pyTree):

```

# - tetraMesher (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Post.PyTree as P
import Transform.PyTree as T

a = G.cart((0,0,0), (1,1,1), (3,3,3))
ext = P.exteriorFaces(a)
ext = C.convertArray2Tetra(ext)
ext = G.close(ext)
ext = T.reorder(ext, (-1,))
m = G.tetraMesher(ext, algo=1)
C.convertPyTree2File(m, 'out.cgns')

```

`Generator.TFI([imin, imax, jmin, jmax, kmin, kmax])`

Generate a mesh by transfinite interpolation (TFI). Generated mesh can be 2D or 3D structured, or unstructured TRI or PENTA mesh. Warning: the boundaries can be in a different order from the examples below, except for the PENTA TFI meshes. 2D structured mesh is built from imin, imax, jmin, jmax boundaries. 3D structured mesh is built from imin, imax, jmin, jmax, kmin, kmax boundaries. Dimensions must be equal for each pair (imin,imax), (jmin,jmax)... TRI mesh is built from imin, jmin, diag boundaries. Each boundary is a structured array with the same dimension. PENTA mesh is built from Tmin, Tmax triangles boundary and imin, imax, diag boundaries. Tmin, Tmax must be structured triangles of dimension nxn. imin, jmin, diag must be structured n*p arrays.

Parameters

- **imin** (array) – I-direction minimum boundary
- **imax** (array) – I-direction maximum boundary

- **jmin** (array) – J-direction minimum boundary
- **jmax** (array) – J-direction maximum boundary
- **kmin** (array) – K-direction minimum boundary
- **kmax** (array) – K-direction maximum boundary
- **diag** (array) – third direction boundary for TRI or PENTA meshes

Returns

2D or 3D mesh

Return type

array or pyTree

Example of use:

- TFI mesh generation (array):

```
# - TFI 2D structured (array)
# - TFI 3D structured (array)
# - TFI TRI (array)
import Converter as C
import Generator as G
import Geom as D
import Transform as T

#-----
# TFI 2D structured
#-----
P0 = (0,0,0); P1 = (5,0,0); P2 = (0,7,0); P3 = (5,7,0)

# Geometrie
d1 = D.line(P0, P1); d2 = D.line(P2, P3)

pts = C.array('x,y,z',5,1,1)
x = pts[1][0]; y = pts[1][1]; z = pts[1][2]
x[0] = 0.; y[0] = 0.; z[0] = 0.
x[1] = -2.; y[1] = 2.; z[1] = 0.
x[2] = -3.; y[2] = 3.; z[2] = 0.
x[3] = 2.; y[3] = 5.; z[3] = 0.
x[4] = 0.; y[4] = 7.; z[4] = 0.
b1 = D.bezier(pts)

pts = C.array('x,y,z',5,1,1)
x = pts[1][0]; y = pts[1][1]; z = pts[1][2]
x[0] = 5.; y[0] = 0.; z[0] = 0.
```

(continues on next page)

(continued from previous page)

```

x[1] = 3.; y[1] = 2.; z[1] = 0.
x[2] = 2.; y[2] = 3.; z[2] = 0.
x[3] = 6.; y[3] = 5.; z[3] = 0.
x[4] = 5.; y[4] = 7.; z[4] = 0.
b2 = D.bezier( pts )

C.convertArrays2File([d1, d2, b1, b2], "geom.plt")

# Regular discretisation of each line
Ni = 20
Nj = 10
r = G.cart((0,0,0), (1./(Ni-1),1,1), (Ni,1,1))
q = G.cart((0,0,0), (1./(Nj-1),1,1), (Nj,1,1))
r1 = G.map(d1, r)
r2 = G.map(d2, r)
r3 = G.map(b1, q)
r4 = G.map(b2, q)

# TFI 2D
m = G.TFI([r1, r2, r3, r4])
C.convertArrays2File([r1,r2,r3,r4,m], 'tfi2d.plt')

#-----
# TFI 3D structured
#-----
xo = 0.; yo = 0.; zo = 0.
nx = 21; ny = 21; nz = 21
hx = 1./(nx-1); hy = 1./(ny-1); hz = 1./(nz-1)

# z = cste
fzmin = G.cart((xo,yo,zo), (hx,hy,1.), (nx,ny,1))
fzmax = T.translate(fzmin, (0.,0.,1.))

# x = cste
fxmin = G.cart((xo,yo,zo), (1,hy,hz), (1,ny,nz))
fxmin = T.reorder(fxmin, (3,1,2))
fxmax = T.translate(fxmin, (1.,0.,0.))

# y = cste
fymin = G.cart((xo,yo,zo), (hx,1.,hz), (nx,1,nz))
fymin = T.reorder(fymin, (1,3,2))
fymax = T.translate(fymin, (0.,1.,0.))

```

(continues on next page)

(continued from previous page)

```

r = [fxmin,fxmax,fymin,fymax,fzmin,fzmax]
m = G.TFI(r)
C.convertArrays2File(r+[m], 'tfi3d.plt')

#-----
# TFI TRI
#-----
l1 = D.line((0,0,0),(0,1,0), 15)
l2 = D.line((0,0,0),(1,0,0), 15)
l3 = D.line((1,0,0),(0,1,0), 15)
tri = G.TFI([l1,l2,l3])
C.convertArrays2File([tri], 'tfitri.plt')

```

- TFI mesh generation (pyTree):

```

# - TFI (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

# Geometry
P0 = (0,0,0); P1 = (5,0,0); P2 = (0,7,0); P3 = (5,7,0)
Ni = 20; Nj = 10
d1 = D.line(P0, P1,Ni); d2 = D.line(P2, P3,Ni)
d3 = D.line(P0, P2,Nj); d4 = D.line(P1, P3,Nj)
m = G.TFI([d1, d2, d3, d4])
C.convertPyTree2File(m, 'out.cgns')

```

Generator.**TFITri**(*a1*, *a2*, *a3*)

Generate three structured meshes by transfinite interpolation around three given curves *a1*, *a2*, *a3*. $N3-N2+N1$ must be odd.

Parameters

- **a1** (array) – first curve
- **a2** (array) – second curve
- **a3** (array) – third curve

Returns

2D structured mesh

Return type

array or pyTree

Example of use:

- TFI structured mesh generation between three curves (array):

```
# - TFITri (array)
import Converter as C
import Generator as G
import Geom as D

P0 = (0,0,0); P1 = (5,0,0); P2 = (1,7,0)

# 3 curves (dont need to be lines)
d1 = D.line(P0, P1, N=11)
d2 = D.line(P1, P2, N=11)
d3 = D.line(P0, P2, N=11)
r = G.TFITri(d1, d2, d3)
C.convertArrays2File(r, 'out.plt')
```

- TFI structured mesh generation between three curves (pyTree):

```
# - TFITri (pyTree)
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

P0 = (0,0,0); P1 = (5,0,0); P2 = (1,7,0)

# 3 curves (dont need to be lines)
d1 = D.line(P0, P1, N=11)
d2 = D.line(P1, P2, N=11)
d3 = D.line(P0, P2, N=11)
r = G.TFITri(d1, d2, d3)
C.convertPyTree2File(r, 'out.cgns')
```

Generator.**TFIO**(*a*, *weight=None*)

Generate five meshes by transfinite interpolation around one given curve *a*. The number of points of *a* must be odd.

Parameters

- **a** (array or zone) – curve

- **weight** (None, float or list of floats) – if provided, the weight sets the size of the inside square

Returns

2D structured mesh (butterfly O-H topology)

Return type

array or pyTree

Example of use:

- Butterfly structured mesh generation by TFI (array):

```
# - TFI0 (array) -
import Converter as C
import Generator as G
import Geom as D

a = D.circle((0,0,0), 1., N=41)
r = G.TFI0(a)
C.convertArrays2File(r, 'out.plt')
```

- Butterfly structured mesh generation by TFI (pyTree):

```
# - TFI0 (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

a = D.circle((0,0,0), 1., N=41)
r = G.TFI0(a)
C.convertPyTree2File(r, 'out.cgns')
```

Generator.TFIHalf0(a1, a2)

Generate four meshes by transfinite interpolation around two given curves a1 and a2 forming a half-O. N1, the number of points of a1 and N2, the number of points of a2 must be odd.

Parameters

- **a1** (array or Zone) – first curve
- **a2** (array or Zone) – second curve

Returns

2D structured mesh (half butterfly C-H topology)

Return type

array or Zone

Example of use:

- Half-Butterfly structured mesh generation by TFI (array):

```
# - TFIHalf0 (array) -
import Converter as C
import Generator as G
import Geom as D

a1 = D.circle((0,0,0), 1., tetas=0, tetae=180., N=41)
a2 = D.line((-1,0,0),(1,0,0), N=21)
r = G.TFIHalf0(a1, a2)
C.convertArrays2File(r, 'out.plt')
```

- Half-Butterfly structured mesh generation by TFI (pyTree):

```
# - TFIHalf0 (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

a1 = D.circle((0,0,0), 1., tetas=0, tetae=180., N=41)
a2 = D.line((-1,0,0),(1,0,0), N=21)
r = G.TFIHalf0(a1, a2)
C.convertPyTree2File(r, 'out.cgns')
```

Generator.**TFIMono**(a1, a2)

Generate one mesh by transfinite interpolation around two given curves a1 and a2 forming a half-O. N1-N2 must be even.

Parameters

- **a1** (array) – first curve
- **a2** (array) – second curve

Returns

2D structured mesh

Return type

array or pyTree

Example of use:

- TFI structured mesh generation between two curves (array):

```
# - TFIMono (array) -
import Converter as C
import Generator as G
import Geom as D

a1 = D.circle((0,0,0), 1., tetas=0, tetae=180., N=41)
a2 = D.line((-1,0,0),(1,0,0), N=21)
r = G.TFIMono(a1, a2)
C.convertArrays2File(r, 'out.plt')
```

- TFI structured mesh generation between two curves (pyTree):

```
# - TFIMono (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

a1 = D.circle((0,0,0), 1., tetas=0, tetae=180., N=41)
a2 = D.line((-1,0,0),(1,0,0), N=21)
r = G.TFIMono(a1, a2)
C.convertPyTree2File(r, 'out.cgns')
```

Generator.TFIStar(a)

Generate a set of meshes by transfinite interpolation a list of given curves.

Parameters

a (list of structured arrays or zones) – input curves

Returns

list of 2D structured mesh

Return type

arrays or pyTree

Example of use:

- TFI structured mesh generation of a set of curves (array):

```
# - TFIStar (array)
import Converter as C
import Generator as G
import Geom as D
```

(continues on next page)

(continued from previous page)

```

P0 = (0,0,0); P1 = (5,0,0); P2 = (7,3,0); P3 = (4,5,0); P4 = (-2,2,0)

# 5 curves (dont need to be lines)
d1 = D.line(P0, P1, N=11)
d2 = D.line(P1, P2, N=11)
d3 = D.line(P2, P3, N=11)
d4 = D.line(P3, P4, N=11)
d5 = D.line(P4, P0, N=11)

r = G.TFIStar([d1,d2,d3,d4,d5])
C.convertArrays2File(r, 'out.plt')

```

- TFI structured mesh generation of a set of curves (pyTree):

```

# - TFIStar (pyTree)
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

P0 = (0,0,0); P1 = (5,0,0); P2 = (7,3,0); P3 = (4,5,0); P4 = (-2,2,0)

# 5 curves (dont need to be lines)
d1 = D.line(P0, P1, N=11)
d2 = D.line(P1, P2, N=11)
d3 = D.line(P2, P3, N=11)
d4 = D.line(P3, P4, N=11)
d5 = D.line(P4, P0, N=11)

r = G.TFIStar([d1,d2,d3,d4,d5])
C.convertPyTree2File(r, 'out.cgns')

```

Generator.**hyper2D**(*line*, *distrib*, "C")

Generate an hyperbolic mesh (2D) of “C” or “O” type from a from a line defined by *line* and from a distribution defined by *distrib*. The resulting mesh is nearly orthogonal.

Parameters

- **line** (array) – starting line of the hyperbolic mesh
- **distrib** (array) – distribution orthogonal to the line

Returns

2D structured mesh

Return type

array or pyTree

Example of use:

- Hyperbolic structured mesh generation from a line (array):

```
# - hyper2D (array) -
import Geom as D
import Generator as G
import Converter as C

msh = D.naca(12., 5001)

# Distribution
Ni = 300; Nj = 50
distrib = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))
a = G.hyper2D(msh, distrib, "C")
C.convertArrays2File([a], 'out.plt')
```

- Hyperbolic structured mesh generation from a line (pyTree):

```
# - hyper2D (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
import Converter.PyTree as C

line = D.naca(12., 5001)
# Distribution
Ni = 300; Nj = 50
distrib = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))

a = G.hyper2D(line, distrib, "C")
C.convertPyTree2File(a, 'out.cgns')
```

Generator.PolyLine.**polyLineMesher**(*a, h, hf, density*)

Generate a 2D mesh around a 2D polyline where *a* is the input polyline (BAR-array), *h* is the height of the mesh, *hf* is the height of the first cell and *density* is the number of points per unity of length. In the 'array' version, it returns a list where B[0] is the list of generated meshes, B[1] is the list of wall boundaries, B[2] is the list of overlap boundaries, B[3] is *h*, B[4] is *density* (eventually modified by the mesher). In the pyTree version, it returns a list [zones,hs,densities], where zones is a list of zones of a CGNS python tree, containing the blocks, wall boundaries, match and overlap

boundaries; `hs` is the list of heights (modified if necessary), and `densities` the list of densities (also modified if necessary).

Parameters

- `a` (BAR-array) – input polyline
- `h` (float) – height of the mesh
- `hf` (float) – first cell size
- `density` (integer) – number of points per unity of length

Returns

2D structured mesh

Return type

array or pyTree

Example of use:

- Structured mesh generation from a polyline (array):

```
# - polyLineMesher (array) -
import Converter as C
import Generator.PolyLine as GP
import Generator as G
import Transform as T

# Read a 2D geometry created with tecplot
a = C.convertFile2Arrays('fusee.plt')
a = G.close(a,1e-2); a = T.reorder(a,(-1,2,3))
C.convertArrays2File(a, 'input.plt')

# Data
h = 0.02; hf = 0.0001; density = 500

# Per families
coords = []; walls = []
for i in a:
    b = GP.polyLineMesher(i, h, hf, density)
    coords.append(b[0])
    walls.append(b[1])

# Flat
meshes = []
for i in coords: meshes = meshes + i

C.convertArrays2File(meshes, 'out.plt')
```

- Structured mesh generation from a polyline (pyTree):

```
# - polyLineMesher (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Transform.PyTree as T

tb = C.convertFile2PyTree('fusee.plt')
tb = G.close(tb,1e-2); tb = T.reorder(tb,(-1,2,3))
h = 0.02; hf = 0.0001; density = 500

res = G.polyLineMesher(tb[2][1][2][0], h, hf, density)
zones = res[0]; h = res[1]; density = res[2]
t = C.newPyTree(['PolyC1']); t[2][1][2] += zones
C.convertPyTree2File(t, 'out.cgns')
```

Generator.PolyC1.**polyC1Mesher**(*A*, *h*, *hf*, *density*, *splitCrit*=10.)

Generate a 2D mesh around a 2D polyC1 curve where *A* is a list of i-arrays each representing a C1 curve. All i-arrays put together must represent a polyC1 curve. *SplitCrit* is a curvature radius triggering split. Other arguments are similar to `polyLineMesher`. The function return is also similar to `polyLineMesher`.

Parameters

- **A** (list of arrays) – list of 1D curves
- **h** (float) – height of the mesh
- **hf** (float) – first cell size
- **density** (integer) – number of points per unity of length
- **splitCrit** (float) – threshold curvature radius below which the initial curve is split

Returns

2D structured mesh

Return type

array or pyTree

Example of use:

- Structured mesh generation from a C1 line (array):

```
# - polyC1Mesher (array) -
import Converter as C
```

(continues on next page)

(continued from previous page)

```

import Generator.PolyC1 as GP
import Generator as G
import Transform as T

# Read geometry from svg file
a = C.convertFile2Arrays('Data/curve.svg', density=1)[0]
a = T.homothety(a, (0,0,0), 0.01)
a = T.reorder(a, (1,2,3))

h = 0.2; hp = 0.001; density = 10.; splitCrit = 2.
m = GP.polyC1Mesher(a, h, hp, density, splitCrit)

for i in m[0]:
    v = G.getVolumeMap(i)
    min = C.getMinValue(v, 'vol')
    if min <= 0:
        print('negative volume detected.')

C.convertArrays2File(m[0], 'out.plt')

```

- Structured mesh generation from a C1 line (pyTree):

```

# - polyC1Mesher (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Transform.PyTree as T

tb = C.convertFile2PyTree('curve1.svg', nptsCurve=100, nptsLine=400)
z = T.homothety(tb[2][1][2][0], (0.,0.,0.), 0.01)
z = T.reorder(z, (-1,2,3))
h = 0.1; hf = 0.001; density = 100; splitCrit = 10.
res = G.polyC1Mesher(z, h, hf, density, splitCrit)
zones = res[0]; h = res[1]; density = res[2]
t = C.newPyTree(['Base']); t[2][1][2] += zones
C.convertPyTree2File(t, 'out.cgns')

```

Generator.**pointedHat**(a, (x, y, z))

Create a structured mesh from a curve defined by a i-array and a point. For the pyTree version: if a contains a solution, it is not taken into account in b.

Parameters

- **a** (array) – closed 1D curve
- **(x,y,z)** (3-tuple of floats) – coordinates of point

Returns

2D structured mesh

Return type

array or pyTree

Example of use:

- 2D closing mesh generation from a closed curve and a point (array):

```
# - pointedHat (array) -
import Geom as D
import Generator as G
import Converter as C
c = D.circle( (0,0,0), 1., 360., 0., 100)
surf = G.pointedHat(c,(0.,0.,1.))
C.convertArrays2File([surf], 'out.plt')
```

- 2D closing mesh generation from a closed curve and a point (pyTree):

```
# - pointedHat (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
import Converter.PyTree as C
c = D.circle( (0,0,0), 1., 360., 0., 100)
surf = G.pointedHat(c,(0.,0.,1.))
t = C.newPyTree(['Base']); t[2][1][2].append(surf)
C.convertPyTree2File(t, 'out.cgns')
```

Generator.**stitchedHat**(*a*, (*offx*, *offy*, *offz*), *tol*=1.e-6, *tol2*=1.e-5)

Create a stitched mesh from a curve defined by a i-array. The surface is stitched in the middle. Tol is the accuracy of the search, tol2 is a merging tolerance and offx, offy, off z an optional offset. For the pyTree version: if a contains a solution, it is not taken into account in b.

Parameters

- **a** (array) – closed 1D curve
- **(offx,offy,offz)** (3-tuple of floats) – coordinates of offset vector
- **tol** (float) – accuracy of search

- **tol2** (float) – merging tolerance

Returns

2D structured mesh

Return type

array or pyTree

Example of use:

- 2D stitched mesh generation from a closed curve (array):

```
# - stitchedHat (array) -
import Geom as D
import Generator as G
import Transform as T
import Converter as C

c = D.circle( (0,0,0), 1., 360., 0., 100)
c = T.contract(c, (0,0,0), (0,1,0), (0,0,1), 0.1)
c = G.stitchedHat(c, (0,0,0), 1.e-3)
C.convertArrays2File([c], 'out.plt')
```

- 2D stitched mesh generation from a closed curve (pyTree):

```
# - stitchedHat (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
import Transform.PyTree as T
import Converter.PyTree as C

c = D.circle((0,0,0), 1., 360., 0., 100)
c = T.contract(c, (0,0,0), (0,1,0), (0,0,1), 0.1)
c = G.stitchedHat(c, (0,0,0), 1.e-4)
C.convertPyTree2File(c, 'out.cgns')
```

Generator.**surfaceWalk**(*surfaces*, *c*, *dj*, *constraints=[]*, *niter=0*, *alphaRef=180.*, *check=0*, *toldist=1.e-6*)

Surface extrusion starting from a curve, resulting into a surface mesh. *dj* is the distribution of points in the extrusion direction starting from *c*, *niter* the number of smoothing iterations. *check=1* means that the extrusion stops at the layer before cells intersect *alphaRef* is the deviation angle wrt 180 degrees enabling to stop the extrusion before it crosses a sharp edge on the surface. *toldist* is a tolerance below which points are considered matching. Constraints can be set as 1D zones.

Parameters

- **surfaces** (list of arrays) – list of surfaces
- **c** (array or pyTree) – starting curve for the extrusion
- **dj** (1D-array) – distribution of points for the extrusion
- **constraints** (list of arrays) – 1D curves constraining the extrusion
- **niter** (integer) – number of smoothing iterations
- **alphaRef** (float) – deviation angle (in degrees) stopping the extrusion
- **check** (integer) – activation key for stopping the extrusion (0 or 1)
- **toldist** (float) – merging points tolerance

Returns

2D structured mesh

Return type

array or pyTree

Example of use:

- 2D mesh extrusion from a curve and walking on a surface (array):

```
# - surfaceWalk (array)
import Converter as C
import Geom as D
import Transform as T
import Generator as G

# User definition of parametric curve
def f(t,u):
    x = t+u; y = t*t+1+u*u; z = u
    return (x,y,z)

# Array definition of geometry
a = D.surface(f)

c = D.circle((1.2,1.7,0.6), 0.1,N=100)
c = T.rotate(c, (1.2,1.7,0.6), (0,1,0), 90.)
c = T.reorder(c, (-1,2,3))
c = T.projectOrtho(c, [a])

h = G.cart((0.,0.,0.), (0.01,1,1), (30,1,1))
```

(continues on next page)

(continued from previous page)

```
r = G.surfaceWalk([a], c, h, niter=100)
C.convertArrays2File([a,c,r], "out.plt")
```

- 2D mesh extrusion from a curve and walking on a surface (pyTree):

```
# - surfaceWalk (pyTree)
import Converter.PyTree as C
import Geom.PyTree as D
import Transform.PyTree as T
import Generator.PyTree as G

# User definition of parametric curve
def f(t,u):
    x = t+u; y = t*t+1+u*u; z = u
    return (x,y,z)

# Array definition of geometry
a = D.surface(f)

c = D.circle((1.2,1.7,0.6), 0.1)
c = T.rotate(c, (1.2,1.7,0.6), (0,1,0), 90.)
c = T.reorder(c, (-1,2,3))
c = T.projectOrtho(c,[a])

h = G.cart((0.,0.,0.), (0.01,1,1), (15,1,1))
r = G.surfaceWalk([a], c, h, niter=100)
C.convertPyTree2File(r, "out.cgns")
```

Generator.**collarMesh**(*s1*, *s2*, *dj*, *dk*, *niterj*=100, *niterk*=100, *ext*=5, *alphaRef*=30.,
type='union', *contour*=[], *constraints1*=[], *constraints2*=[],
toldist=1.e-10, *topology*='overset')

Create a collar mesh at junction(s) between two surfaces *s1* and *s2* in union or difference assembly, using a distribution along the surface *dj* and a distribution in the normal direction to the wall *dk*. *niterj* and *niterk* are the number of smoothing iterations for *j* and *k* directions. *ext* is the extension of the collar mesh for difference assembly. *type* is the assembly type, and can be 'union' or 'difference'. *alphaRef* is the deviation angle wrt 180 degrees above which the walk is stopped. *contour* is the starting contour to create the collar grids, *constraints1* and *constraints2* are 1D zones defining the curves the collar grid must follow on surfaces *s1* and *s2* respectively. *toldist* is the matching point tolerance. Parameter 'topology' can be 'overset' or 'extruded', only useful in case of difference. Topology set to 'overset' results in two

overlapping collar grids, whereas it results in a collar grid extruded from the surface grid in the other case.

Parameters

- **s1** (array or pyTree) – surface
- **s2** (array or pyTree) – surface
- **dj** (1D-array) – distribution of points along surfaces
- **dk** (1D-array) – distribution of points in the normal direction
- **niterj** (integer) – number of smoothing iterations in j direction
- **niterk** (integer) – number of smoothing iterations in k direction
- **ext** (integer) – extension of collar for difference assembly
- **alphaRef** (float) – deviation angle (in degrees) stopping the extrusion
- **type** (string) – type of the assembly (union or difference)
- **contour** (list of arrays) – starting curve for the collar creation
- **constraints1** (list of arrays) – 1D curves constraining the collar on s1 surface
- **constraints2** (list of arrays) – 1D curves constraining the collar on s2 surface
- **toldist** (float) – merging points tolerance
- **topology** (string) – choice of collar mesh topology (overset or extruded) in case of difference assembly

Returns

3D structured mesh

Return type

array or pyTree

Example of use:

- 3D collar mesh between two surfaces (array):

```
# - collarMesh (array) -
import Converter as C
import Geom as D
import Transform as T
import Generator as G
```

(continues on next page)

(continued from previous page)

```
s1 = D.sphere((0.,0.,0.),1,20)
s2 = T.translate(s1,(1.2,0.,0.)); s2 = T.homothety(s2,(0,0,0),0.5)
dhj = G.cart((0.,0.,0.),(1.e-2,1,1),(21,1,1))
dhk = G.cart((0.,0.,0.),(1.e-2,1,1),(11,1,1))
a = G.collarMesh(s1,s2, dhj,dhk,niterj=100,niterk=100,type='union')
C.convertArrays2File(a,"out.plt")
```

- 3D collar mesh between two surfaces (pyTree):

```
# - collarMesh (pyTree)
import Converter.PyTree as C
import Geom.PyTree as D
import Transform.PyTree as T
import Generator.PyTree as G

s1 = D.sphere((0.,0.,0.),1,20)
s2 = T.translate(s1,(1.2,0.,0.)); s2 = T.homothety(s2,(0,0,0),0.5)
dhj = G.cart((0.,0.,0.),(1.e-2,1,1),(21,1,1))
dhk = G.cart((0.,0.,0.),(1.e-2,1,1),(11,1,1))
a = G.collarMesh(s1,s2, dhj,dhk,niterj=100,niterk=100,type='union')
C.convertPyTree2File(a,"out.cgns")
```

3.3 Cartesian grid generators

Generator.**gencartmb**(*A*, *h*, *Dfar*, *nlvl*)

Simple Cartesian generator. Create a set of Cartesian grids (B) around a list of body grids (A). Those grids are patched with a ratio of 2. The user controls the number of levels, and the number of points for each level of grid. *h* is the spatial step on the finest level. *Dfar* is the maximal distance to the body. *nlvl* is a list that provides the number of points per level (*nlvl*[0]: finest grid), except for the finest level.

Parameters

- **A** (array/list of arrays or pyTree/list of pyTrees) – body grids
- **h** (float) – spatial step in the finest level
- **Dfar** (float) – maximal distance to the body A
- **nlvl** (list of integers) – list of number of points per level (except the finest one)

Returns

2D/3D structured mesh

Return type

array or pyTree

Example of use:

- Generation of Cartesian mesh refined near body grids (array):

```
# - gencartmb (array) -
import Generator as G
import Converter as C

# body grid
a = G.cylinder((0.,0.,0.), 0.5, 1., 360., 0., 10., (50,50,30))
h = 1.e-1# Step of finest Cartesian grid
Dfar = 10.# Extension of far boundaries
nlvl = [5,5,5] # Nb of points per level, except the 4th level_
↳(automatic)
cartGrids = G.gencartmb([a], h, Dfar, nlvl)
C.convertArrays2File(cartGrids, 'out.plt')
```

- Generation of Cartesian mesh refined near body grids (pyTree):

```
# - gencartmb (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

# body mesh
a = G.cylinder((0.,0.,0.), 0.5, 1., 360., 0., 10., (50,50,30))
h = 1.e-1 # Step of finest Cartesian grid
Dfar = 20. # Distance to far boundaries

# Nb of points per level:
# Here 4 levels, but last one is computed automatically
nlvl = [10,10,5] # nlvl[0]: coarse grid

t = C.newPyTree(['Bodies', 'CARTESIAN']); t[2][1][2].append(a)
zones = G.gencartmb(t[2][1], h, Dfar, nlvl)
t[2][2][2] += zones
C.convertPyTree2File(t, 'out.cgns')
```

Generator.**octree**(surfs, snearList=[], dfarList=[], dfar=-1., balancing=0,
levelMax=1000, ratio=2, octant=None)

Create a QUAD quadtree mesh in 2D or an HEXA octree mesh in 3D starting from a list of bodies and snears. Each parameter snear is the required spatial step of the octree near the corresponding body; the extension of the domain can be provided by dfar, starting from the global bounding box of all surfaces defined by surfs. A list of extensions can be provided in dfarList, in order not to take into account a surface in the computation of the bounding box. It must be set to -1 for the surface that must not be taken into account. Parameter balancing=1 means that the octree is balanced, i.e. adjacent elements are at worst twice as big/small; levelMax is the maximum number of levels required. If ratio=2, then a classical octree mesh is built. If ratio=3, a 27-tree mesh is built, in which case the spacing ratio is 3 (and not 2) between two adjacent elements. Parameter balancing enables to balance the octree; balancing=0 means no balancing; balancing=1 means a classical balancing, whereas balancing=2 takes also into account elements sharing a common vertex.

Parameters

- **surfs** (list of arrays/pyTrees) – body grids
- **snears** (list of floats) – list of spatial step near the corresponding body
- **dfar** (float) – maximal distance to the body grids
- **balancing** (integer) – activation key for balanced octree (0, 1 or 2)
- **levelMax** (integer) – maximum number of levels
- **ratio** (integer) – spacing ratio between two adjacent elements

Returns

2D/3D unstructured mesh

Return type

array or pyTree

Example of use:

- [Generation of unstructured octree mesh refined near body grids \(array\)](#):

```
# - octree (array) -
import Generator as G
import Converter as C
import Geom as D

s = D.circle((0,0,0), 1., N=100); snear = 0.01
res = G.octree([s], [snears], dfar=5., balancing=2)
C.convertArrays2File([res], 'out.plt')
```

- Generation of unstructured octree mesh refined near body grids (pyTree):

```
# - octree (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

s = D.circle((0,0,0), 1., N=100); snear = 0.1
res = G.octree([s], [snear], dfar=5.)
C.convertPyTree2File(res, 'out.cgns')
```

`Generator.octree2Struct`(*octree*, *vmin*=15, *ext*=0, *optimized*=1, *merged*=1, *AMR*=0, *sizeMax*=1000000)

Convert an octree or a quadtree mesh into a set of Cartesian grids. Parameter *ext* is the extension of Cartesian grids in all the directions; *vmin* can be an integer defining the number of points in each Cartesian grid, or a list of integers, defining the number of points per refinement level. In that case, the first element of the list of *vmin* defines the finest level. Specifying all the levels is not mandatory. If *optimized*=1, the *ext* value is reduced by -1 at overlap borders for the coarsest grid for minimum overlapping. If *merged*=1, Cartesian grids are merged in order to reduce the number of created grids. If *AMR*=1, a set of AMR zones are generated. Parameter *sizeMax* can be used when merging is applied: in that case, the number of points per grid does not exceed *sizeMax*. Warning: to obtain multigrid blocks, *optimized* must be set to 0.

Parameters

- **octree** (array or pyTree) – input unstructured octree grid
- **vmin** (integer or list of integers) – number of points in all Cartesian grids or list of number of points for each octree level
- **ext** (integer) – extension of Cartesian grids (0 = no extension, N = extension of N cells in all direction)
- **optimized** (integer) – activation key for optimization of coarsest grid (0 or 1)
- **merged** (integer) – activation key for automatic merging of Cartesian grids
- **AMR** (integer) – activation key for AMR generation (0 or 1)
- **sizeMax** (integer) – maximum number of points in Cartesian grids after merging

Returns

2D/3D structured mesh

Return type

array or pyTree

Example of use:

- Generation of structured Cartesian mesh from an octree grid (array):

```
# - octree2Struct (array) -
import Generator as G
import Converter as C
import Geom as D

s = D.circle((0,0,0), 1., N=100); snear = 0.1
res = G.octree([s],[snear], dfar=5., balancing=1)
res = G.octree2Struct(res, vmin=5, ext=2, optimized=1)
C.convertArrays2File([s]+res, "out.plt")
```

- Generation of structured Cartesian mesh from an octree grid (pyTree):

```
# - octree2Struct (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

s = D.circle((0,0,0), 1., N=100); snear = 0.1
res = G.octree([s],[snear], dfar=5., balancing=1)
res = G.octree2Struct(res, vmin=5, ext=2,merged=1)
C.convertPyTree2File(res, 'out.cgns')
```

Generator.**adaptOctree**(*octree, indicator, balancing=1, ratio=2*)

Adapt an unstructured octree with respect to an indicator field located at element centers. If ‘indicator’ is strictly positive for an element, then the element must be refined as many times as required by the indicator number. If ‘indicator’ is strictly negative, the element is coarsened if possible as many times as required by the indicator number. If ‘indicator’ is 0., the element remains unchanged. *balancing=1* means that the octree is balanced after adaptation. If *ratio=2*, then a classical octree mesh is built. If *ratio=3*, a 27-tree mesh is built, in which case the spacing ratio is 3 (and not 2) between two adjacent elements. For array interface indicator is an array, for pyTree version, indicator is the name of field stored as a solution located at centers. Exists also as in place version (*_adaptOctree*) that modifies a and returns None.

Parameters

- **octree** (array or pyTree) – input unstructured octree grid

- **indicator** (array or variable name in the pyTree) – field of values to indicate where to refine, coarsen or maintain the octree grid
- **balancing** (integer) – activation key for balanced octree (0, 1 or 2, see the definition of octree function for the meaning)
- **ratio** (integer) – spacing ratio between two adjacent elements

Returns

modified reference copy of t

Return type

same as input

Example of use:

- Adaptation of an octree grid wrt. indicator (array):

```
# - adaptOctree (array) -
import Generator as G
import Converter as C
import Geom as D

s = D.circle((0,0,0), 1., N=100); snear = 0.1
o = G.octree([s], [snear], dfar=5., balancing=1)
indic = C.node2Center(o)
indic = C.initVars(indic, 'indicator', 1.)
res = G.adaptOctree(o, indic)
C.convertArrays2File([o,res], "out.plt")
```

- Adaptation of an octree grid wrt. indicator (pyTree):

```
# - adaptOctree (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

s = D.circle((0,0,0), 1., N=100); snear = 0.1
o = G.octree([s], [snear], dfar=5., balancing=1)
o = C.initVars(o, 'centers:indicator', 1.)
res = G.adaptOctree(o)
C.convertPyTree2File(res, 'out.cgns')
```

Generator.**expandLayer**(*octree*, *level=0*, *corners=0*, *balancing=0*)

Expand the layer of given level for an octree unstructured mesh. If *corners=1*, expand also in corners directions. Exists also as in place version (`_expandLayer`) that modifies *a* and returns `None`.

Parameters

- **octree** (array or pyTree) – input unstructured octree grid
- **level** (integer) – level to be expanded (level=0 is the finest)
- **corners** (integer) – activation key for expansion in corners (0 or 1)
- **balancing** (integer) – activation key for balanced octree (0, 1 or 2, see the definition of octree function for the meaning)

Returns

modified reference copy of *t*

Return type

same as input

Example of use:

- Expansion of user-specified level in an octree grid (array):

```
# - expandLayer (array) -
import Generator as G
import Converter as C
import Geom as D

s = D.circle((0.,0.,0.), 1., N=100)
o = G.octree([s], [0.1], dfar=1., balancing=1)
o2 = G.expandLayer(o, level=0)
C.convertArrays2File([o, o2], "out.plt")
```

- Expansion of user-specified level in an octree grid (pyTree):

```
# - expandLayer (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

s = D.circle((0.,0.,0.),1.,N=100)
o = G.octree([s], [0.1], dfar=1., balancing=1)
o2 = G.expandLayer(o, level=0)
C.convertPyTree2File(o2, 'out.cgns')
```

Generator.PyTree.**cartRx**(*X0, H, N, Nb, depth=0, addCellN=False, addBCMatch=False, rank=None, size=None*)

Create a set of regular cartesian grids. If *depth* > 0, an overlap of *depth* cells is added between grids. When used in parallel, the set of grids is distributed.

Parameters

- **X0** (tuple of 3 floats) – first point coordinates
- **H** (tuple of 3 floats) – steps of grids
- **N** (tuple of 3 integers) – number of points in each direction for each block
- **Nb** (tuple of 3 floats) – number of blocks in each direction
- **depth** (integer) – number of overlap cells between cartesian grids
- **addCellN** (boolean) – if True and *depth* > 0, add *cellN* field
- **addBCMatch** (boolean) – if True and *depth*=0, create *BCMatch*
- **rank** (integer) – current rank when running in parallel
- **size** (integer) – current number of procs when running in parallel

Returns

regular cartesian set of grids

Return type

list of zones

Example of use:

- Generation of a set of regular cartesian grids (pyTree):

```
# - cartRx (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cartRx((0,0,0), (1,1,1), (30,30,30), (5,5,5), depth=0,
↪addCellN=False)
C.convertPyTree2File(a, 'out.cgns')
```

Generator.PyTree.**cartRx3**(*XC0, XC1, HC, XF0, XF1, R, dim=3, rank=None, size=None*)

Create a set of regular and geometric cartesian grids with double steps. The mesh is made of a regular cartesian core and border grids are geometric cartesian grids. When used in parallel, the set of grids is distributed.

Parameters

- **XC0** (tuple of 3 floats) – first point of cartesian core
- **XC1** (tuple of 3 floats) – last of of cartesian core
- **HC** (tuple of 3 floats) – core cartesian steps
- **XF0** (tuple of 3 floats) – first point of geometric region
- **XF1** (tuple of 3 floats) – last point of geometric region
- **R** (tuple of 3 floats) – geometric factor in each direction
- **dim** (2 or 3) – space dimension
- **rank** (integer) – current rank when running in parallel
- **size** (integer) – current number of procs when running in parallel

Returns

cartesian set of grids

Return type

list of zones

Example of use:

- Generation of a set of regular and geometric cartesian grids (pyTree):

```
# - cartRx3 (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cartRx3((0,0,0), (10,10,10), (0.1,0.1,0.1), (-10,-10,-10), (30,20,
↪20), (1.1,1.1,1.1))

C.convertPyTree2File(a, 'out.cgns')
```

3.4 Operations on meshes

`Generator.close(a, tol=1.e-12)`

Close a mesh defined by array a. Points that are distant of tol maximum to one another are merged.

Exists also as in place version (`_close`) that modifies a and returns None.

Parameters

- **a** (array or pyTree) – input mesh

- **tol** (float) – merging points tolerance

Returns

modified reference copy of t

Return type

array or pyTree

Example of use:

- Mesh closing (array):

```
# - close (array) -
import Converter as C
import Generator as G

a = G.cylinder((0.,0.,0.), 0.5, 1., 360., 0.01, 10., (20,20,10))
a = C.convertArray2Tetra(a)
a = G.close(a, 1.e-3)
C.convertArrays2File(a, 'out.plt')
```

- Mesh closing (pyTree):

```
# - close (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G

a1 = G.cart((0,0,0), (1,1,1), (10,10,1))
a2 = G.cart((9+1.e-2,0,0), (1,1,1), (10,10,1))
a3 = G.cart((0,-5.01,0), (1,1,1), (19,6,1))
a4 = G.cart((0,9.0001,0), (1,1,1), (10,6,1))
a5 = G.cart((9.01,9.0002,0), (1,1,1), (10,6,1))
t = C.newPyTree(['Base', 2, a1, a2, a3, a4, a5])
t = G.close(t, 1.e-1)
C.convertPyTree2File(t, 'out.cgns')
```

Generator.**selectInsideElts**(a, curves)

Select elements of a TRI-array, whose centers are inside the given list of curves, defined by BAR-arrays.

Parameters

- **a** (array or pyTree) – input triangle 2D mesh
- **curves** (array or list of arrays) – list of curves

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Selection of TRI cells inside a specified curve (array):

```
# - selectInsideElts (array) -
import Converter as C
import Generator as G
import Geom as D

a = G.cart( (0,0,0), (1,1,1), (10,10,1)); a = C.convertArray2Tetra(a)
b = D.circle( (5,5,0), 3.); b = C.convertArray2Tetra(b)
a = G.selectInsideElts(a, [b])
C.convertArrays2File([a,b], 'out.plt')
```

- Selection of TRI cells inside a specified curve (pyTree):

```
# - selectInsideElts (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

a = G.cart((0,0,0), (1,1,1), (10,10,1))
a = C.convertArray2Tetra(a)
b = D.circle((5,5,0), 3.)
b = C.convertArray2Tetra(b)
a = G.selectInsideElts(a, b)
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**map**(*a*, *distrib*, *dir*)

Map a distribution on a curve or on a structured surface. Map a i-array distribution in a direction (*dir*=1,2,3) in a surface or volume mesh.

Parameters

- **a** (array or pyTree) – 1D/2D/3D structured mesh
- **distrib** (array) – distribution of points
- **dir** (integer) – direction i/j/k for the distribution (*dir*=1,2,3)

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Map distribution (array):

```
# - map (array) -
import Geom as D
import Generator as G
import Converter as C

# Map on a curve
l = D.line( (0,0,0), (1,1,0) )
Ni = 10
d = G.cart( (0,0,0), (1./(Ni-1),1.,1.), (Ni,1,1) )
m = G.map(l, d)
C.convertArrays2File([m], "out1.plt")

# Map on a structured surface
ni = 2; nj = 3
a = G.cart((0,0,0), (1,1,1), (ni,nj,1))
C.setValue(a, (1,1,1), [1.,1.,2.])
C.setValue(a, (1,2,1), [1.,2.,5.])
C.setValue(a, (1,3,1), [1.,3.,2.])
C.setValue(a, (2,1,1), [2.,1.,2.])
C.setValue(a, (2,2,1), [2.,2.,5.])
C.setValue(a, (2,3,1), [2.,3.,2.])
b = D.bezier(a, 10, 10)
Ni = 50; Nj = 30
d = G.cart( (0,0,0), (1./(Ni-1),1./(Nj-1),1.), (Ni,Nj,1) )
d = G.enforceX(d, 0.5, 0.01, (10,20))
d = G.enforceY(d, 0.5, 0.01, (10,20))
b = G.map(b, d)
C.convertArrays2File(b, "out2.plt")

# Map in a direction
a = G.cylinder((0,0,0), 0.5, 2., 0, 60, 1., (20,20,1))
Ni = 10
d = G.cart( (0,0,0), (1./(Ni-1),1.,1.), (Ni,1,1) )
d = G.enforcePlusX(d, 0.01, (10,20))
a = G.map(a, d, 2)
C.convertArrays2File(a, "out3.plt")
```

- Map distribution (pyTree):

```
# - map (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
import Converter.PyTree as C

l = D.line( (0,0,0), (1,1,0) )
Ni = 11; dist = G.cart( (0,0,0), (1./(Ni-1),1.,1.), (Ni,1,1) )
l = G.map(l, dist)
t = C.newPyTree(['Base',1,1])
C.convertPyTree2File(t, 'out.cgns')
```

Generator.**mapSplit**(*a*, *distrib*, *splitCrit*=100.)

Split a i-array and map a distribution on the splitted i-array. SplitCrit is the curvature radius triggering split.

Parameters

- **a** (array or pyTree) – 1D/2D/3D structured mesh
- **distrib** (array) – distribution of points
- **splitCrit** (float) – curvature radius for array splitting

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Split and map distribution (array):

```
# - mapSplit (array) -
import Generator as G
import Converter as C
import Geom as D

# polyline
a = D.polyline([(0,0,0),(1,0,0),(1,1,0),(2,3,0),(1.5,3,0),(1,1.5,0),(0,0,
↪0)])
# distribution
Ni = 41
dist = G.cart((0,0,0),(1./(Ni-1),1,1),(Ni,1,1))
```

(continues on next page)

(continued from previous page)

```

dist = G.enforceX(dist, 15.5/(Ni-1), 0.005, 2,5)
dist = G.enforceX(dist, 27.5/(Ni-1), 0.005, 2,5)
a = G.mapSplit(a,dist,0.25)
C.convertArrays2File(a, 'out.plt')

```

- Split and map distribution (pyTree):

```

# - mapSplit (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

# polyline
a = D.polyline([(0,0,0),(1,0,0),(1,1,0),(2,3,0),(1.5,3,0),(1,1.5,0),(0,0,
↪0)])
# distribution
Ni = 41
dist = G.cart((0,0,0),(1./(Ni-1),1,1),(Ni,1,1))
dist = G.enforceX(dist, 15.5/(Ni-1), 0.005, 2,5)
dist = G.enforceX(dist, 27.5/(Ni-1), 0.005, 2,5)
zones = G.mapSplit(a,dist,0.25)
t = C.newPyTree(['Base',1]); t[2][1][2] += zones
C.convertPyTree2File(t, 'out.cgns')

```

`Generator.refine(a, power, dir)`

Refine a structured array. The original distribution is kept but the number of points is multiplied by power. Dir is the direction of refinement (1, 2, 3). If dir=0, refine in all directions.

Exists also as in place version (`_refine`) that modifies a and returns None.

Parameters

- **a** ([array] or [zone]) – 1D/2D/3D structured mesh
- **power** (float) – multiplication factor of number of points
- **dir** (integer) – direction i/j/k for the distribution (dir=0,1,2,3)

Return type

Identical to a

Example of use:

- Structured mesh refinement (array):

```
# - refine (array) -
import Generator as G
import Converter as C

a = G.cart( (0,0,0), (0.1,0.1,0.1), (20,20,1) )

a = G.refine(a, 1.5, 1)
C.convertArrays2File([a], 'out.plt')
```

- Structured mesh refinement (pyTree):

```
# - refine (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cart( (0,0,0), (0.1,0.1,0.1), (20,20,1) )
a = G.refine(a, 1.5, 1)
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**mapCurvature**(*a*, *N*, *power*, *dir*)

Map a structured array following the curvature. *N* is the final number of points. *Dir* is the direction of remeshing (1, 2, 3).

Parameters

- **a** ([array] or [zone]) – 1D/2D structured mesh
- **N** (integer) – number of points after new distribution
- **power** (float) – refinement factor
- **dir** (integer) – direction i/j/k for the distribution (dir=1,2,3)

Return type

Identical to *a*

Example of use:

- Map distribution wrt. curvature (array):

```
# - mapCurvature (array) -
import Generator as G
import Converter as C
import Geom as D
```

(continues on next page)

(continued from previous page)

```

ni = 2; nj = 3
a = G.cart((0,0,0), (1,1,1), (ni,nj,1))
C.setValue(a, (1,1,1), [1.,1.,2.])
C.setValue(a, (1,2,1), [1.,2.,4.])
C.setValue(a, (1,3,1), [1.,3.,2.])
C.setValue(a, (2,1,1), [2.,1.,2.])
C.setValue(a, (2,2,1), [2.,2.,5.])
C.setValue(a, (2,3,1), [2.,3.,2.])
b = D.bezier(a, density=10.)

b = G.mapCurvature(b, N=100, power=0.5, dir=1)
C.convertArrays2File([b], 'out.plt')

```

- Map distribution wrt. curvature (pyTree):

```

# - mapCurvature (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

ni = 2; nj = 3
a = G.cart((0,0,0), (1,1,1), (ni,nj,1))
C.setValue(a, 'GridCoordinates', (1,1,1), [1.,1.,2.])
C.setValue(a, 'GridCoordinates', (1,2,1), [1.,2.,5.])
C.setValue(a, 'GridCoordinates', (1,3,1), [1.,3.,2.])
C.setValue(a, 'GridCoordinates', (2,1,1), [2.,1.,2.])
C.setValue(a, 'GridCoordinates', (2,2,1), [2.,2.,5.])
C.setValue(a, 'GridCoordinates', (2,3,1), [2.,3.,2.])
b = D.bezier(a, density=10.)

b = G.mapCurvature(b, N=100, power=0.5, dir=1)

C.convertPyTree2File(b, 'out.cgns')

```

Generator.densify(a, h)

Densify a i-array or a BAR-array with a new discretization step h. Discretization points from the original array are kept.

Exists also as in place version (`_densify`) that modifies a and returns None.

Parameters

- a ([array] or [zone]) – 1D structured mesh

- **h** (float) – new cell size step for the points densification

Return type

Identical to a

Example of use:

- Curve densification (array):

```
# - densify (array) -
import Generator as G
import Converter as C
import Geom as D

a = D.circle((0,0,0), 1., 10)
b = G.densify(a, 0.01)
C.convertArrays2File(b, 'out.plt')
```

- Curve densification (pyTree):

```
# - densify (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

a = D.circle((0,0,0), 1., 10)
b = G.densify(a, 0.01)
C.convertPyTree2File(b, 'out.cgns')
```

Generator.grow(a, vector)

Grow a surface array of one layer. Vector is the node displacement. For the array version, vector is defined by an array. For the PyTree version, vector = ['v1','v2','v3'] where variables 'v1', 'v2', 'v3' are defined as solutions in a, located at nodes.

Parameters

- **a** (array or Zone) – 2D surface mesh
- **vector** (array or list of 3 variables contained in the solution) – vector of node displacement

Returns

new 3D structured mesh

Return type

array or Zone

Example of use:

- Extrusion of one layer from a surface mesh (array):

```
# - grow (array) -
import Converter as C
import Generator as G
import Geom as D

a = D.sphere( (0,0,0), 1., 50 )
n = G.getNormalMap(a)
n = C.center2Node(n); n[1] = n[1]*100.
b = G.grow(a, n)
C.convertArrays2File([b], 'out.plt')
```

- Extrusion of one layer from a surface mesh (pyTree):

```
# - grow (pyTree)-
import Converter.PyTree as C
import Converter.Internal as Internal
import Generator.PyTree as G
import Geom.PyTree as D

a = D.sphere((0,0,0), 1., 50)
a = G.getNormalMap(a)
a = C.center2Node(a, Internal.__FlowSolutionCenters__)
a = C.rmVars(a, Internal.__FlowSolutionCenters__)
b = G.grow(a, ['sx', 'sy', 'sz'])
t = C.newPyTree(['Base1', 2, 'Base2', 3])
t[2][1][2].append(a); t[2][2][2].append(b)
C.convertPyTree2File(t, 'out.cgns')
```

Generator.**stack**(a, b=None)

Can stack 1D meshes with same topology into 2D meshes. Can stack 2D meshes with same topology into 3D meshes.

Parameters

- **a** (array, zone or list of arrays, zones) – a mesh or a list of topologically identical meshes
- **b** (array, zone) – a mesh

Returns

a mesh

Return type

array or Zone

Example of use:

- Mesh generation by stacking two meshes (array):

```
# - stack (array) -
import Generator as G
import Converter as C
import Transform as T
import Geom as D

# Concatenate 2 structured grids
a = G.cylinder((0,0,0), 1, 1.3, 360, 0, 1., (50,10,1))
b = T.rotate(a, (0,0,0), (1,0,0), 5.)
b = T.translate(b, (0,0,0.5))
c = G.stack(a, b)

# Concatenate a list of structured grids
a = []
for i in range(10):
    a.append(D.circle((0,0,i), 1.))
c = G.stack(a)

C.convertArrays2File(c, 'out.plt')
```

- Mesh generation by stacking two meshes (pyTree):

```
# - stack (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Transform.PyTree as T

a = G.cylinder((0,0,0), 1, 1.3, 360, 0, 1., (50,10,1))
b = T.rotate(a, (0,0,0), (1,0,0), 5.)
b = T.translate(b, (0,0,0.5))
c = G.stack(a, b)
C.convertPyTree2File(c, 'out.cgns')
```

Generator.**addNormalLayers**(a, d, check=0, niter=0)

Normal extrusion from a surface mesh. d is a 1D distribution providing the height of each layer. If check=1, the extrusion stops before negative volume cells are created. Niter specifies the number of iterations for normals smoothing.

Parameters

- **a** (array or pyTree) – 2D surface mesh
- **d** (1D array) – distribution of normal extrusion
- **check** (integer) – activation key for negative volume criteria (0 or 1)
- **niter** (integer) – number of iterations for normals smoothing

Returns

new 3D structured mesh

Return type

array or pyTree

Example of use:

- Normal extrusion from a surface mesh (array):

```
# - addNormalLayers (array) -
import Generator as G
import Converter as C
import Geom as D

d = C.array('d', 3, 1, 1)
d[1][0,0] = 0.1; d[1][0,1] = 0.2; d[1][0,2] = 0.3
a = D.sphere( (0,0,0), 1, 50 )
a = G.addNormalLayers(a, d, niter=20)
C.convertArrays2File([a], 'out.plt')
```

- Normal extrusion from a surface mesh (pyTree):

```
# - addNormalLayers (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

d = G.cart((0.,0.,0.), (0.1,1,1),(3,1,1))
a = D.sphere((0,0,0), 1, 50)
b = G.addNormalLayers(a, d)
C.convertPyTree2File(b, 'out.cgns')
```

`Generator.TTM(a, niter=100)`

Smooth a mesh using elliptic generator.

Parameters

- **a** (array or pyTree) – 2D structured mesh
- **niter** (integer) – number of smoothing iterations

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- 2D structured mesh smoothing (array):

```
# - TTM (array) -
import Converter as C
import Generator as G
import Geom as D

P0 = (0,0,0); P1 = (5,0,0); P2 = (0,7,0); P3 = (5,7,0)

# Geometry
d1 = D.line(P0, P1); d2 = D.line(P2, P3)
pts = C.array('x,y,z', 5, 1, 1)
x = pts[1][0]; y = pts[1][1]; z = pts[1][2]

x[0] = 0. ; y[0] = 0. ; z[0] = 0.
x[1] = -2. ; y[ 1 ] = 2. ; z[1] = 0.
x[2] = -3. ; y[ 2 ] = 3. ; z[2] = 0.
x[3] = 2. ; y[ 3 ] = 5. ; z[3] = 0.
x[4] = 0. ; y[ 4 ] = 7. ; z[4] = 0.
b1 = D.bezier(pts)

x[0] = 5. ; y[ 0 ] = 0. ; z[ 0 ] = 0.
x[1] = 3. ; y[ 1 ] = 2. ; z[ 1 ] = 0.
x[2] = 2. ; y[ 2 ] = 3. ; z[ 2 ] = 0.
x[3] = 6. ; y[ 3 ] = 5. ; z[ 3 ] = 0.
x[4] = 5. ; y[ 4 ] = 7. ; z[ 4 ] = 0.
b2 = D.bezier( pts )
C.convertArrays2File([d1, d2, b1, b2], 'geom.plt')

# Regular discretisation of each line
Ni = 20; Nj = 10
r = G.cart((0,0,0), (1./(Ni-1),1,1), (Ni,1,1))
q = G.cart((0,0,0), (1./(Nj-1),1,1), (Nj,1,1))
```

(continues on next page)

(continued from previous page)

```

r1 = G.map(d1, r)
r2 = G.map(d2, r)
r3 = G.map(b1, q)
r4 = G.map(b2, q)

# TTM
m = G.TFI([r1, r2, r3, r4])
m2 = G.TTM(m, 2000)
C.convertArrays2File([m,m2], 'out.plt')

```

- 2D structured mesh smoothing (pyTree):

```

# - TTM (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

P0 = (0,0,0); P1 = (5,0,0); P2 = (0,7,0); P3 = (5,7,0)

# Geometry
d1 = D.line(P0,P1); d2 = D.line(P2,P3)
d3 = D.line(P0,P2); d4 = D.line(P1,P3)

# Regular discretisation of each line
Ni = 20; Nj = 10
r = G.cart((0,0,0), (1./(Ni-1),1,1), (Ni,1,1))
q = G.cart((0,0,0), (1./(Nj-1),1,1), (Nj,1,1))
r1 = G.map(d1, r); r2 = G.map(d2, r)
r3 = G.map(d3, q); r4 = G.map(d4, q)

# TTM
m = G.TFI([r1, r2, r3, r4])
m = G.TTM(m)
t = C.newPyTree(['Base',2]); t[2][1][2].append(m)
C.convertPyTree2File(t, 'out.cgns')

```

Generator.**snapFront**(*a*, *S*, *optimized=1*)

Snap a mesh to a surface *S*. A front must be defined in a by a cellN field. Points of this front are snapped to the surface. If *optimized=0*, the exterior front cellN=1 is snapped, else if *optimized=1* optimized front cellN=1 is snapped, else if *optimized=2*, front cellN=0 is snapped.

Exists also as in place version (`_snapFront`) that modifies `a` and returns `None`.

Parameters

- `a` (array or `pyTree`) – 3D mesh
- `S` (list of zones) – surface mesh
- `optimized` (integer) – optimization key (0,1,2)

Returns

new unstructured mesh

Return type

array or `pyTree`

Example of use:

- Mesh snapping to a surface (array):

```
# - snapFront (array) -
import Generator as G
import Converter as C
import Geom as D
import Connector as X
import Transform as T

s = D.circle((0,0,0), 1., N=100)
s = T.addkplane(s)

# Grille cartesienne (reguliere)
BB = G.bbox([s])
ni = 100; nj = 100; nk = 3
xmin = BB[0]; ymin = BB[1]; zmin = BB[2]-0.5
xmax = BB[3]; ymax = BB[4]; zmax = BB[5]+0.5
hi = (xmax-xmin)/(ni-1); hj = (ymax-ymin)/(nj-1)
h = min(hi, hj)
ni = int((xmax-xmin)/h)+7; nj = int((ymax-ymin)/h)+7
b = G.cart((xmin-3*h, ymin-3*h, zmin), (h, h, 1.), (ni,nj,nk))
celln = C.array('cellN', ni, nj, nk)
celln = C.initVars(celln, 'cellN', 1.)

# Masquage
cellno = X.blankCells([b], [celln], [s], blankingType=0, delta=0., dim=2)
a = C.initVars(s, 'cellN', 1)
b = C.addVars([b, cellno[0]])

# Adapte le front de la grille a la surface
```

(continues on next page)

(continued from previous page)

```

b = T.subzone(b, (1,1,2), (b[2],b[3],2))
b = G.snapFront(b, [s])

C.convertArrays2File([a,b], 'out.plt')

```

- Mesh snapping to a surface (pyTree):

```

# - snapFront (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D
import Connector.PyTree as X
import Transform.PyTree as T
import Converter.Internal as Internal

s = D.circle((0,0,0), 1., N=100)
s2 = T.addkplane(s)

# Grille cartesienne (reguliere)
BB = G.bbox([s])
ni = 100; nj = 100; nk = 3
xmin = BB[0]; ymin = BB[1]; zmin = BB[2]-0.5
xmax = BB[3]; ymax = BB[4]; zmax = BB[5]+0.5
hi = (xmax-xmin)/(ni-1); hj = (ymax-ymin)/(nj-1)
h = min(hi, hj)
ni = int((xmax-xmin)/h)+7; nj = int((ymax-ymin)/h)+7
b = G.cart( (xmin-3*h, ymin-3*h, zmin), (h, h, 1.), (ni,nj,nk) )
t = C.newPyTree(['Cart'])
t[2][1][2].append(b)

# Masquage
t = C.initVars(t, 'cellN', 1)
import numpy
BM = numpy.array([[1]])
t = X.blankCells(t, [[s2]], BM, blankingType='node_in', dim=2)

# Adapte le front de la grille a la surface
dim = Internal.getZoneDim(b)
t = T.subzone(t, (1,1,2), (dim[1],dim[2],2))
t = G.snapFront(t, [s2])

t = C.addBase2PyTree(t, 'Surface', cellDim=2)

```

(continues on next page)

(continued from previous page)

```
s2 = C.initVars(s2, 'cellN', 1)
t[2][2][2].append(s2)

C.convertPyTree2File(t, 'out.cgns')
```

Generator.**snapSharpEdges**(*a*, *S*, *step=None*, *angle=30*.)

Snap a mesh to a surface *S*, constrained by sharp edges and corners. if *step* != *None*, sharp edges are refined with this step. Sharp Edges are calculated depending on *angle*.

Exists also as in place version (`_snapSharpEdges`) that modifies *a* and returns *None*.

Parameters

- **a** (array or pyTree) – mesh to be deformed
- **S** (list of zones) – surface mesh
- **step** (float) – step for sharp edges refinement
- **angle** (float) – angle (in degrees) for sharp edges detection

Returns

new unstructured mesh

Return type

array or pyTree

Example of use:

- Mesh snapping to sharp edges of a surface (array):

```
# - snapSharpEdges (array) -
import Generator as G
import Converter as C
import Post as P
import Geom as D

# Enforce polyline define by s in b
s = D.polyline([(0.2,0,0),(1,1,0),(2.5,1,0),(0.2,0,0)])
s = C.initVars(s, 'indic', 0)
h = 0.1
ni = 30; nj = 20; nk=1
b = G.cartHexa((-0.5, -0.5, 0), (h, h, 1.), (ni,nj,nk))
b = C.initVars(b, 'indic', 0)
b = G.snapSharpEdges(b, [s], h)
```

(continues on next page)

(continued from previous page)

```

c = C.converter.convertQuad2Tri(b)
C.convertArrays2File([b,c, s], 'out.plt')

# Same with smooth
#c = T.smooth(c, eps=0.5, niter=5,
#           fixedConstraints=s)
#           #projConstraints=s)C

# Enforce all constraints (must be over-refined)
s = D.circle((0,0,0), R=1, N=400)
s = C.initVars(s, 'indic', 0)
h = 0.3
ni = 10; nj = 20; nk=1
b = G.cartHexa((-1.5, -1.5, 0), (h, h, 1.), (ni,nj,nk))
b = C.initVars(b, 'indic', 0)
b = G.snapSharpEdges(b, [s], 0.1*h)
c = C.converter.convertQuad2Tri(b)
C.convertArrays2File([b,c,s], 'out.plt')
import sys; sys.exit()

# Idem external
h = 0.3
ni = 10; nj = 10; nk=1
s = G.cartHexa((-1.6,-1.6,0), (h/2,h/2,1.), (2*ni+2,2*nj+2,nk))
s = P.exteriorFaces(s)
s = C.initVars(s, 'indic', 0)
b = G.cartHexa((-1.5, -1.5, 0), (h, h, 1.), (ni,nj,nk))
b = C.initVars(b, 'indic', 0)
b = G.snapSharpEdges(b, [s], h*0.1)
C.convertArrays2File([b,s], 'out.plt')

```

- Mesh snapping to sharp edges of a surface (pyTree):

```

# - snapSharpEdges (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

# polylignes avec angles vifs
s = D.polyline([(0.02,0,0),(1,1,0),(2,1,0),(0.02,0,0)])
# Grille cartesienne (reguliere)
h = 0.1

```

(continues on next page)

(continued from previous page)

```

ni = 30; nj = 20; nk=1
b = G.cart((-0.5, -0.5, 0), (h, h, 1.), (ni,nj,nk))
b = G.snapSharpEdges(b, [s], h)
t = C.newPyTree(['Cart', 'Surface'])
t[2][1][2].append(b); t[2][2][2].append(s)
C.convertPyTree2File(t, 'out.cgns')

```

3.5 Operation on surface meshes

Generator.**fittingPlaster**(*a*, *bumpFactor*=0.)

Create a structured surface patch that fits a curve *a*. *BumpFactor* controls the curvature of the patch.

Parameters

- **a** (array) – curve to fit
- **bumpFactor** (float) – amplitude of the bump

Returns

created 2D structured mesh

Return type

array or pyTree

Example of use:

- Creation of patch that fits a curve (array):

```

# - fittingPlaster (array) -
import Generator as G
import Converter as C
import Geom as D

a = D.circle( (0,0,0), 1, N=50 )
a = C.convertArray2Tetra(a)
a = G.close(a)
b = G.fittingPlaster(a, bumpFactor=0.5)
C.convertArrays2File([a,b], 'out.plt')

```

- Creation of patch that fits a curve (pyTree):

```
# - fittingPlaster (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

a = D.circle( (0,0,0), 1, N=50 )
a = C.convertArray2Tetra(a)
a = G.close(a)
b = G.fittingPlaster(a, bumpFactor=0.5)
C.convertPyTree2File(b, 'out.cgns')
```

Generator.**gapfixer**(*a*, *c*, *hardPoints*=None, *refine*=1)

Fill a surface defined by a BAR contour *a* drawn on a surface *c*. You can force the generated mesh to pass through given *hardPoints* (NODES). If *refine*=0, no inside points are added.

Parameters

- **a** (BAR array) – contour of the gap
- **c** (array) – surface to be filled
- **hardPoints** (array or list of arrays) – mesh containing nodes to be enforced
- **refine** (integer) – activation key for including points in the gap mesh (0 or 1)

Returns

TRI surface mesh

Return type

array or pyTree

Example of use:

- Surface gap filling from a contour (array):

```
# - gapfixer (array) -
import Generator as G
import Converter as C
import Geom as D

# Fix the gap inside a circle drawn on a plane
a = D.circle((0,0,0), 1, N=100)
a = C.convertArray2Tetra(a); a = G.close(a)
```

(continues on next page)

(continued from previous page)

```

b = G.cart((-2.,-2.,0.), (0.1,0.1,1.), (50,50,1))
a1 = G.gapfixer(a, b)
C.convertArrays2File(a1, 'out.plt')

# Fill the gap in the circle, using one defined point
hp = D.point((0.5, 0.5, 0.))
a2 = G.gapfixer(a, b, hp, refine=0)
C.convertArrays2File(a2, 'outHP.plt')

```

- Surface gap filling from a contour (pyTree):

```

# - gapfixer (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

# Fix the gap inside a circle drawn on a plane
a = D.circle((0,0,0), 1, N=100)
a = C.convertArray2Tetra(a); a = G.close(a)
b = G.cart((-2.,-2.,0.), (0.1,0.1,1.), (50,50,1))
a1 = G.gapfixer(a, b)
C.convertPyTree2File(a1, 'out.cgns')

# Fill the gap in the circle, using one defined point
hp = D.point((0.5, 0.5, 0.))
a2 = G.gapfixer(a, b, hp, refine=0)
C.convertPyTree2File(a2, 'outHP.cgns')

```

Generator.**gapsmanager**(*A*, *mode=0*, *coplanar=0*)

Fill multiple gaps in a set of surface components *A*. Also, eliminate overlap regions between components if any. Normals for all patches must be pointed outwards. Set *mode=0* for nodal mesh, 1 for center mesh, and 2 otherwise. Set *coplanar=1* if all components are lying on a same plane.

Parameters

- **A** (array or pyTree) – surface mesh with gaps
- **mode** (integer) – key for grid location (0 = nodes, 1 = centers, 2 = others)
- **coplanar** (integer) – activation key for coplanar components of *A* (0 or 1)

Returns

new surface mesh

Return type

array or pyTree

Example of use:

- Surface gaps filling (array):

```
# - gapsmanager (array) -
import Geom as D
import Converter as C
import Generator as G

a = D.sphere6((0,0,0), 1, N=10)
a = C.node2Center(a)
a = C.convertArray2Tetra(a)
b = G.gapsmanager(a, mode=2)
C.convertArrays2File(b, 'out.plt')
```

- Surface gaps filling (pyTree):

```
# - gapsmanager (pyTree) -
import Geom.PyTree as D
import Converter.PyTree as C
import Generator.PyTree as G

a = D.sphere6((0,0,0), 1, N=10)
a = C.node2Center(a)
a = C.convertArray2Tetra(a)
b = G.gapsmanager(a, mode=2)
C.convertPyTree2File(b, 'out.cgns')
```

Generator.**mmgs**(*A*, *ridgeAngle*=45., *hmin*=0., *hmax*=0., *hausd*=0.01, *grow*=1.1, *anisotropy*=0, *optim*=0, *fixedConstraints*=[], *sizeConstraints*=[])

Refine a TRI surface mesh using MMGs.

Parameters

- **A** ([array, list of arrays] or [zone, pyTree]) – surface TRI mesh
- **ridgeAngle** (double) – Angle between adjacent cells that MMGs consider to be a ridge (degrees)

- **hmin** (double) – the minimum mesh step in final mesh
- **hmax** (double) – the maximum mesh step in final mesh
- **hausd** (double) – the maximum chordal deviation in final mesh from initial mesh
- **grow** (double) – the maximum difference of steps between two adjacent cells
- **optim** (int) – if 1, only optimize mesh keeping the same number of points
- **fixedConstraints** ([list of arrays] or [list of zones]) – curves or surface identifying points that must be in output mesh
- **sizeConstraints** ([list of arrays] or [list of zones]) – curves or surface defining sizemap

Returns

remeshed surface

Return type

identical to input

Example of use:

- Surface mesh remeshing (array):

```
# - mmgs (array) -
import Geom as D
import Generator as G
import Converter as C

a = D.sphere6( (0,0,0), 1., N=20, ntype='TRI' )

# Optimisation
b = G.mmgs(a, optim=1)
C.convertArrays2File(b, 'out.plt')

# Remaillage avec parametres
b = G.mmgs(a, hausd=0.01, hmax=0.1)
C.convertArrays2File(b, 'out.plt')

# Raffinement avec sizemap
a = C.initVars(a, 'sizemap=0.2*abs({x})+0.05')
b = G.mmgs(a, hausd=10.)
C.convertArrays2File(b, 'out.plt')
```

- Surface mesh remeshing (pyTree):

```
# - mmgs (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
import Converter.PyTree as C

a = D.sphere6( (0,0,0), 1., N=20, ntype='TRI' )

# Optimisation
b = G.mmgs(a, optim=1)
C.convertPyTree2File(b, 'out1.cgns')

# Remaillage avec parametres
b = G.mmgs(a, hausd=0.01, hmax=0.1)
C.convertPyTree2File(b, 'out2.cgns')

# Raffinement avec sizemap
a = C.initVars(a, '{sizemap}=0.2*abs({CoordinateX})+0.05')
b = G.mmgs(a, hausd=10.)
C.convertPyTree2File(b, 'out3.cgns')
```

3.6 Information on generated meshes

Generator.**barycenter**(*a*, *weight=None*)

Return the barycenter of *a*, with optional weight.

Parameters

- **a** (array or pyTree) – input mesh
- **weight** (string) – name of the weight variable in *a*

Returns

coordinates of the barycenter

Return type

3-list of floats

Example of use:

- Computation of the mesh barycenter (array):

```
# - barycenter (array) -
import Generator as G
import Converter as C
a = G.cart((0.,0.,0.), (0.1,0.1,1.), (20,20,20))
print(G.barycenter(a))
#>> [0.9500000000000001, 0.9500000000000005, 9.5]
w = C.initVars(a, 'weight', 1.); w = C.extractVars(w,['weight'])
print(G.barycenter(a, w))
#>> [0.9500000000000001, 0.9500000000000005, 9.5]
```

- Computation of the mesh barycenter (pyTree):

```
# - barycenter (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
a = G.cart((0.,0.,0.), (0.1,0.1,1.), (20,20,20))
print(G.barycenter(a))
#>> [0.9500000000000001, 0.9500000000000005, 9.5]
a = C.initVars(a, 'weight', 1.)
print(G.barycenter(a, 'weight'))
#>> [0.9500000000000001, 0.9500000000000005, 9.5]
```

Generator.**bbox**(a)

Return the bounding box [xmin, ymin, zmin, xmax, ymax, zmax] of a.

Parameters

a (array or pyTree) – input mesh

Returns

coordinates of the bounding box

Return type

6-list of floats

Example of use:

- Computation of the mesh bounding box (array):

```
# - bbox (array) -
import Generator as G
a = G.cart((0.,0.,0.), (0.1,0.1,1.), (20,20,20))
b = G.cart((12.,0.,0.), (0.1,0.1,1.), (20,20,20))
print(G.bbox(a))
```

(continues on next page)

(continued from previous page)

```
print(G.bbox([a, b]))
```

- Computation of the mesh bounding box (pyTree):

```
# - bbox (pyTree) -
import Generator.PyTree as G
a = G.cart((0., 0., 0.), (0.1, 0.1, 1.), (20, 20, 20))
print(G.bbox(a))
```

Generator.bboxOfCells(a)

Return the bounding box of each cell of a. The bounding box field is located at centers of cells.

Exists also as in place version (`_bboxOfCells`) that modifies a and returns None.

Parameters

a (array or pyTree) – input mesh

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Computation of the cell bounding boxes (array):

```
# - bboxOfCells (array) -
import Generator as G
a = G.cart((0., 0., 0.), (0.1, 0.1, 1.), (20, 20, 20))
b = G.bboxOfCells(a)
print(b)
```

- Computation of the cell bounding boxes (pyTree):

```
# - bboxOfCells (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
a = G.cart((0., 0., 0.), (0.1, 0.1, 1.), (20, 20, 20))
a = G.bboxOfCells(a)
C.convertPyTree2File(a, 'out.cgns')
```


Generator.**BB**(a, method='AABB', weighting=0, tol=0.)

Return the bounding box of a as an array or a zone. If method is 'AABB', then it computes the Axis-Aligned Bounding-Box, if method is 'OBB' then it computes the Oriented Bounding-Box. The argument weighting may be 0, and the OBB is computed using a Cloud-Point approach, or 1, and it is computed using a Surface-Weighting approach. If weighting=1, then the provided array must be a surface composed of triangles.

Exists also as in place version (`_BB`) that modifies a and returns None.

Parameters

- **a** (array or pyTree) – input mesh
- **method** (string) – choice between axis-aligned or oriented bounding box
- **weighting** (integer) – activation key for surface weighting approach
- **tol** (float) – extension of bounding box in all the directions

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Bounding box generation (array):

```
# - BB (array) -
import Generator as G
import Converter as C
import Geom as D

s = D.circle((0,0,0), 1., N=100)
a = G.BB(s)
C.convertArrays2File([a,s], 'out.plt')
```

- Bounding box generation (pyTree):

```
# - BB (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
```

(continues on next page)

(continued from previous page)

```
import Geom.PyTree as D

s = D.circle((0,0,0), 1., N=100)
a = G.BB(s); a[0] = 'bbox'
C.convertPyTree2File([s,a], 'out.cgns')
```

Generator.**CEBBI**ntersection(*a1*, *a2*, *tol*=1.e-10)

Test the Cartesian Elements Bounding Box (CEBB) intersection between *a1* and *a2*. Tolerance is a float given by *tol*. Return 0 if no intersection, 1 otherwise.

Parameters

- **a1** (array or pyTree) – input mesh
- **a2** (array or pyTree) – input mesh
- **tol** (float) – tolerance of intersection

Returns

0 if no intersection, 1 otherwise

Return type

integer

Example of use:

- Intersection by Cartesian elements bounding box between two meshes (array):

```
# - CEBBIIntersection (array) -
import Generator as G
import Transform as T
ni = 11; nj = 3; nk = 11
a1 = G.cart((0.,0.,0.), (0.1,0.1,0.2),(ni, nj,nk))
a2 = G.cart((1.,0.,0.), (0.1,0.1,0.2),(ni, nj,nk))
a2 = T.rotate(a2, (0,0,0), (0,0,1), 12.)
print(G.CEBBIIntersection(a1, a2))
```

- Intersection by Cartesian elements bounding box between two meshes (pyTree):

```
# - CEBBIIntersection (pyTree)-
import Generator.PyTree as G
import Transform.PyTree as T

ni = 11; nj = 3; nk = 11
a1 = G.cart((0.,0.,0.), (0.1,0.1,0.2),(ni, nj,nk))
```

(continues on next page)

(continued from previous page)

```
a2 = G.cart((1.,0.,0.), (0.1,0.1,0.2),(ni, nj,nk))
a2 = T.rotate(a2, (0,0,0), (0,0,1), 12.)
print(G.CEBBIIntersection(a1, a2))
```

Generator.**bbboxIntersection**(a1, a2, tol=1.e-6, isBB=False, method='AABB')

Test if a1 and a2 intersects. Three options are available: method='AABB' (intersection between two Axis-Aligned Bounding Boxes, by default); method='OBB' (intersection between two Oriented Bounding Boxes, the most general case); method='AABBBOBB' (intersection between an AABB -a1- and an OBB -a2-).; If a1 and a2 are directly the corresponding bounding boxes, the user may switch isBB=True in order to avoid recalculating them. Return 0 if no intersection, 1 otherwise.

Exists also as in place version (`_bbboxIntersection`) that modifies a1 and returns None.

Parameters

- **a1** (array or pyTree) – input mesh
- **a2** (array or pyTree) – input mesh
- **tol** (float) – tolerance of intersection
- **isBB** (boolean) – activation key if meshes already are bounding boxes
- **method** (string) – intersection method

Returns

0 if no intersection, 1 otherwise

Return type

integer

Example of use:

- Intersection by bounding box between two meshes (array):

```
# - bbboxIntersection (array) -
import Generator as G
ni = 11; nj = 3; nk = 11
a1 = G.cart((0.,0.,0.), (0.1,0.1,0.2),(ni, nj,nk))
a2 = G.cart((0.5,0.05,0.01), (0.1,0.1,0.2),(ni, nj,nk))
intersect = G.bbboxIntersection(a1,a2); print(intersect)
```

- Intersection by bounding box between two meshes (pyTree):

```
# - bboxIntersection (pyTree) -
import Generator.PyTree as G
ni = 11; nj = 3; nk = 11
a1 = G.cart((0.,0.,0.), (0.1,0.1,0.2),(ni, nj,nk))
a2 = G.cart((0.5,0.05,0.01), (0.1,0.1,0.2),(ni, nj,nk))
intersect = G.bboxIntersection(a1, a2); print(intersect)
```

Generator.**checkPointInCEBB**(a, (x, y, z))

Test if a given point is in the CEBB of a.

Parameters

- a (array or pyTree) – input mesh
- (x,y,z) (3-tuple of floats) – coordinates of point

Returns

0 if point is not in the CEBB of a, 1 otherwise

Return type

integer

Example of use:

- Detection of point location in the bounding box of a mesh (array):

```
# - checkPointInCEBB (array) -
import Generator as G
import Transform as T

Ni = 20; Nj = 20
a1 = G.cart((0,0,0), (1./Ni,0.5/Nj,1), (Ni,Nj,2))
a2 = G.cart((-0.1,0,0), (0.5/Ni, 0.5/Nj, 1), (Ni,Nj,2))
a2 = T.rotate(a2, (-0.1,0,0), (0,0,1), 0.22)

# Check if point is in CEBB of mesh2
val = G.checkPointInCEBB(a2, (0.04839, 0.03873, 0.5)); print(val)
```

- Detection of point location in the bounding box of a mesh (pyTree):

```
# - checkPointInCEBB (pyTree) -
import Generator.PyTree as G
import Transform.PyTree as T

Ni = 20; Nj = 20
```

(continues on next page)

(continued from previous page)

```

a2 = G.cart((-0.1,0,0),(0.5/Ni, 0.5/Nj, 1), (Ni,Nj,2))
a2 = T.rotate(a2, (-0.1,0,0), (0,0,1), 0.22)

# Check if point is in CEBB of a2
val = G.checkPointInCEBB(a2, (0.04839, 0.03873, 0.5)); print(val)

```

Generator.getVolumeMap(a)

Return the volume field of an array. Volume is located at centers of cells.

Exists also as in place version (`_getVolumeMap`) that modifies `a` and returns `None`.

Parameters

`a` (array or pyTree) – input volume or surface mesh

Returns

modified reference copy of `a`

Return type

array or pyTree

Example of use:

- Computation of cells volume (array):

```

# - getVolumeMap (array) -
import Generator as G
import Converter as C

a = G.cart((0.,0.,0.), (0.1,0.1,0.2), (10,10,3))
vol = G.getVolumeMap(a)
vol = C.center2Node(vol); vol = C.addVars([a, vol])
C.convertArrays2File(vol, "out.plt")

```

- Computation of cells volume (pyTree):

```

# - getVolumeMap (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cart((0.,0.,0.), (0.1,0.1,0.2), (10,10,3))
a = G.getVolumeMap(a)
C.convertPyTree2File(a, 'out.cgns')

```

Generator.**getNormalMap**(a)

Return the surface normals field of a surface array. It is located at centers of cells.

Exists also as in place version (`_getNormalMap`) that modifies a and returns None.

Parameters

a (array or pyTree) – input surface mesh

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Computation of surface normals (array):

```
# - getNormalMap (array) -
import Geom as D
import Generator as G
import Converter as C

# 2D structured
a = D.sphere((0,0,0), 1, 50)
n = G.getNormalMap(a)
n = C.center2Node(n);n = C.addVars([a, n])
C.convertArrays2File([n], 'out1.plt')

# 2D unstructured
a = D.sphere((0,0,0), 1, 50)
a = C.convertArray2Tetra(a)
n = G.getNormalMap(a)
n = C.center2Node(n);n = C.addVars([a, n])
C.convertArrays2File([n], 'out2.plt')
```

- Computation of surface normals (pyTree):

```
# - getNormalMap (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
import Converter.PyTree as C

a = D.sphere((0,0,0), 1, 50)
a = G.getNormalMap(a)
C.convertPyTree2File(a, 'out.cgns')
```

Generator.`getSmoothNormalMap(a, niter=2, eps=0.4)`

Return the smoothed surface normals field of a surface array, located at nodes. `niter` is the number of smoothing operations, and `eps` is a smoothing weight.

Exists also as in place version (`_getSmoothNormalMap`) that modifies `a` and returns `None`.

Parameters

- `a` (array or `pyTree`) – input surface mesh
- `niter` (integer) – smoothing iterations number
- `eps` (float) – smoothing weight

Returns

modified reference copy of `a`

Return type

array or `pyTree`

Example of use:

- Computation of surface smoothed normals (array):

```
# - getSmoothNormalMap (array) -
import Converter as C
import Generator as G
import Transform as T

a = G.cart((0.,0.,0.),(1.,1.,1.),(10,10,1))
b = G.cart((0.,0.,0.),(1.,1.,1.),(1,10,10))
b = T.rotate(b,(0.,0.,0.),(0.,1.,0.),45.)
c = C.convertArray2Hexa([a,b])
c = T.join(c); c = T.reorder(c,(1,))
c = T.rotate(c,(0.,0.,0.),(0.,1.,0.),15.)
s = G.getSmoothNormalMap(c, niter=4)
c = C.addVars([c,s])
C.convertArrays2File(c, "out.plt")
```

- Computation of surface smoothed normals (pyTree):

```
# - getSmoothNormalMap (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Transform.PyTree as T
```

(continues on next page)

(continued from previous page)

```

a = G.cart((0.,0.,0.),(1.,1.,1.),(10,10,1))
b = G.cart((0.,0.,0.),(1.,1.,1.),(1,10,10))
b = T.rotate(b,(0.,0.,0.),(0.,1.,0.),45.)
c = C.convertArray2Hexa([a,b])
c = T.join(c); c = T.reorder(c,(1,))
c = T.rotate(c,(0.,0.,0.),(0.,1.,0.),15.)
c = G.getSmoothNormalMap(c, niter=4)
C.convertPyTree2File(c, "out.cgns")

```

Generator.getOrthogonalityMap(a)

Return the orthogonality map of an array. The orthogonality map corresponds to the maximum deviation of all dihedral angles of an element. The orthogonality map is expressed in degree and located at centers.

Exists also as in place version (`_getOrthogonalityMap`) that modifies `a` and returns `None`.

Parameters

`a` (array or pyTree) – input mesh

Returns

modified reference copy of `a`

Return type

array or pyTree

Example of use:

- Computation of cells orthogonality (array):

```

# - getOrthogonalityMap (array) -
import Generator as G
import Converter as C

a = G.cylinder((0.,0.,0.), 0.5, 1., 360., 0., 10., (50,50,10))
ac = C.node2Center(a)
ortho = G.getOrthogonalityMap(a)
ortho = C.addVars([ac, ortho])
C.convertArrays2File([ortho], "out.plt")

```

- Computation of cells orthogonality (pyTree):


```
# - getOrthogonalityMap (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cylinder((0.,0.,0.), 0.5, 1., 360., 0., 10., (50,50,10))
a = G.getOrthogonalityMap(a)
C.convertPyTree2File(a, 'out.cgns')
```

Generator.getRegularityMap(a)

Return the regularity map of an array. The regularity map corresponds to the maximum deviation of the volume ratio of an element and all its neighbouring cells. The regularity map is located at centers in a field “regularity”.

Exists also as in place version (`_getRegularityMap`) that modifies a and returns None. Exists also as parallel distributed version (`G.Mpi.getRegularityMap`).

Parameters

a (array or pyTree) – input mesh

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Computation of cells regularity with respect to volumes (array):

```
# - getRegularityMap (array) -
import Generator as G
import Converter as C

a = G.cart( (0,0,0), (1,1,1), (50,50,1))
a = G.enforceX(a, 25, 0.1, 10, 10)
ac = C.node2Center(a)
reg = G.getRegularityMap(a)
reg = C.addVars([ac, reg])
C.convertArrays2File([reg], "out.plt")
```

- Computation of cells regularity with respect to volumes (pyTree):

```
# - getRegularityMapPT (pyTree) -
import Generator.PyTree as G
```

(continues on next page)

(continued from previous page)

```

import Converter.PyTree as C

a = G.cart((0,0,0), (1,1,1), (50,50,1))
a = G.enforceX(a, 25, 0.1, 10, 10)
a = G.getRegularityMap(a)
C.convertPyTree2File(a, 'out.cgns')

```

Generator.`getAngleRegularityMap`(*a*)

Return the angle regularity map of an array. The angle regularity map corresponds to the maximum angle difference between an element and its neighbouring cells. The angle regularity map is expressed in degree and located at centers in a field “regularityAngle”.

Exists also as in place version (`_getAngleRegularityMap`) that modifies *a* and returns None. Exists also as parallel distributed version (`G.Mpi.getAngleRegularityMap`).

Parameters

a (array or pyTree) – input mesh

Returns

modified reference copy of *a*

Return type

array or pyTree

Example of use:

- Computation of cells regularity with respect to angles (array):

```

# - getAngleRegularityMap (array) -
import Generator as G
import Converter as C
import Transform as T

a = G.cart((0,0,0), (1,1,1), (50,50,1))
a = T.deformPoint(a, (25,25,0), (1.,1.,0.), 2., 2.)
ac = C.node2Center(a)
reg = G.getAngleRegularityMap(a)
reg = C.addVars([ac, reg])
C.convertArrays2File([reg], "out.plt")

```

- Computation of cells regularity with respect to angles (pyTree):

```
# - getAngleRegularityMap (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Transform.PyTree as T

a = G.cart((0,0,0), (1,1,1), (50,50,1))
a = T.deformPoint(a, (25,25,0), (1.,1.,0.), 2., 2.)
a = G.getAngleRegularityMap(a)
C.convertPyTree2File(a, 'out.cgns')
```

Generator.getTriQualityMap(a)

Return the quality map of a TRI array. The triangle quality is a value between 0. (degenerated triangle) and 1. (equilateral triangle). The quality map is located at centers.

Exists also as in place version (`_getTriQualityMap`) that modifies a and returns None.

Parameters

a (array or pyTree) – input surface TRI mesh

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Computation of triangles quality (array):

```
# - getTriQualitylityMap (array) -
import Generator as G
import Converter as C
import Geom as D

a = D.sphere( (0,0,0), 1, N=10 )
a = C.convertArray2Tetra(a); a = G.close(a)
n = G.getTriQualityMap(a)
n = C.center2Node(n); n = C.addVars([a, n])
C.convertArrays2File([n], "out.plt")
```

- Computation of triangles quality (pyTree):

```
# - getTriQualitylityMap (PyTree) -
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

a = D.sphere((0,0,0), 1, N=10)
a = C.convertArray2Tetra(a)
a = G.close(a)
t = C.newPyTree(['Base',2,a])
t = G.getTriQualityMap(t)
C.convertPyTree2File(t, 'out.cgns')
```

Generator.**getCellPlanarity**(a)

Return a measure of cell planarity for each cell. It is located at centers of cells.

Exists also as in place version (`_getCellPlanarity`) that modifies a and returns None.

Parameters

a (array or pyTree) – input surface mesh

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Computation of cells planarity (array):

```
# - getCellPlanarity (array) -
import Converter as C
import Generator as G
import Geom as D

a = D.sphere( (0,0,0), 1., 10)
p = G.getCellPlanarity(a)
p = C.center2Node(p); a = C.addVars([a, p])
C.convertArrays2File([a], 'out.plt')
```

- Computation of cells planarity (pyTree):

```
# - getCellPlanarity (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G
import Geom.PyTree as D

a = D.sphere((0,0,0), 1., 10)
a = G.getCellPlanarity(a)
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**getCircumCircleMap**(a)

Return the map of circum circle radius of any cell of a ‘TRI’ array.

Exists also as in place version (`_getCircumCircleMap`) that modifies a and returns None.

Parameters

a (array or pyTree) – input surface mesh

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Computation of cells circumscribed circle radius (array):

```
# - getCircumCircleMap (array) -
import Geom as D
import Generator as G
import Converter as C

a = D.sphere((0,0,0), 1, 50)
a = C.convertArray2Tetra(a)
n = G.getCircumCircleMap(a)
n = C.center2Node(n); n = C.addVars([a, n])
C.convertArrays2File([n], "out.plt")
```

- Computation of cells circumscribed circle radius (pyTree):

```
# - getCircumCircleMap (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
```

(continues on next page)

(continued from previous page)

```

import Converter.PyTree as C

a = D.sphere((0,0,0), 1, 50)
a = C.convertArray2Tetra(a)
t = C.newPyTree(['Base', 2, a])
t = G.getCircumCircleMap(t)
C.convertPyTree2File(t, 'out.cgns')

```

Generator.getInCircleMap(a)

Return the map of inscribed circle radius of any cell of a ‘TRI’ array.

Exists also as in place version (`_getInCircleMap`) that modifies `a` and returns `None`.

Parameters

`a` (array or pyTree) – input surface mesh

Returns

modified reference copy of `a`

Return type

array or pyTree

Example of use:

- Computation of cells inscribed circle radius (array):

```

# - getInCircleMap (array) -
import Geom as D
import Generator as G
import Converter as C

a = D.sphere((0,0,0), 1, 50)
a = C.convertArray2Tetra(a)
n = G.getInCircleMap(a)
n = C.center2Node(n); n = C.addVars([a, n])
C.convertArrays2File([n], "out.plt")

```

- Computation of cells inscribed circle radius (pyTree):

```

# - getInCircleMap (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
import Converter.PyTree as C

```

(continues on next page)

(continued from previous page)

```

a = D.sphere((0,0,0), 1, 50)
a = C.convertArray2Tetra(a)
t = C.newPyTree(['Base', 2, a])
t = G.getInCircleMap(t)
C.convertPyTree2File(t, 'out.cgns')

```

Generator.getEdgeRatio(a)

Return the ratio between the longest and the smallest edges of a cell.

Exists also as in place version (`_getEdgeRatio`) that modifies `a` and returns `None`.

Parameters

`a` (array or pyTree) – input mesh

Returns

modified reference copy of `a`

Return type

array or pyTree

Example of use:

- Computation of maximum edge ratio of cells (array):

```

# - getEdgeRatio(array) -
import Generator as G
import Converter as C

a = G.cart((0.,0.,0.), (0.1,0.1,0.1), (11,11,11))
a = G.enforcePlusX(a, 1e-6, (5,50))
r = G.getEdgeRatio(a)
r = C.center2Node(r); r = C.addVars([a,r])
C.convertArrays2File([r], "out.plt")

```

- Computation of maximum edge ratio of cells (pyTree):

```

# - getEdgeRatio(pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cart((0.,0.,0.), (0.1,0.1,0.1), (11,11,11))
a = G.enforcePlusX(a, 1e-6, (5,50))
a = G.getEdgeRatio(a)
C.convertPyTree2File(a, "out.cgns")

```

Generator.**getMaxLength**(a)

Return the length of the longer edge of each cell.

Exists also as in place version (`_getMaxLength`) that modifies a and returns None.

Parameters

a (array or pyTree) – input mesh

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Computation of maximum edge length of cells (array):

```
# - getMaxLength(array) -
import Generator as G
import Converter as C

a = G.cart((0.,0.,0.), (0.1,0.1,0.1), (11,11,11))
a = G.enforcePlusX(a,1e-6,(5,50))
r = G.getMaxLength(a)
r = C.center2Node(r); r = C.addVars([a,r])
C.convertArrays2File([r], "out.plt")
```

- Computation of maximum edge length of cells (pyTree):

```
# - getMaxLength(pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

a = G.cart((0.,0.,0.), (0.1,0.1,0.1), (11,11,11))
a = G.enforcePlusX(a,1e-6,(5,50))
a = G.getMaxLength(a)
C.convertPyTree2File(a, "out.cgns")
```

Generator.**checkMesh**(m, critVol=0., critOrtho=15., critReg=0.1, critAngReg=15.,
addGC=False, verbose=0)

Return global information about a given mesh based on four unit tests. Two local tests are used (getVolumeMap and getOrthogonalityMap), as well as two global tests (getRegularityMap and getAngleRegularityMap) to assess the mesh quality.

Parameters

- **m** (array or pyTree) – input mesh
- **critVol,...** (floats) – critical values for each unit test. All critical values are used to check if a value is above a given threshold, except for the first unit test (getVolumeMap) for which we usually check for negative volume cells in the mesh
- **addGC** (Boolean) – if True, add one layer of ghost cells to the pyTree. Useful for global tests (getAngleRegularityMap and getRegularityMap) in the case of multiple zones
- **verbose** (int) – if 2, print mesh info per sub-zone (local min, max, mean values and percentage of critical cells per test). If 1, only print mesh info when critical cells are encountered. If 0, do not print anything

Returns

global min, max and mean values as well as the number of critical cells obtained for each test

Return type

dictionary

Example of use:

- Get global mesh info (array):

```
# - checkMesh (array) -
import Generator as G

a = G.cart((0,0,0), (1,1,1), (10,10,10))
infos = G.checkMesh(a)
print(infos)
#> {'vmin': 1.0, 'vmax': 1.0, 'vmean': 1.0, 'vcrit': 0, 'rmin': 0.0,
    ↪ 'rmax': 0.0, 'rmean': 0.0, 'rcrit': 0, 'amin': 0.0, 'amax': 0.0, 'amean'
    ↪ ': 0.0, 'acrit': 0, 'omin': 0.0, 'omax': 0.0, 'omean': 0.0, 'ocrit': 0}
```

- Get global mesh info (pyTree):

```
# - checkMesh (pyTree) -
import Generator.PyTree as G

a = G.cart((0,0,0), (1,1,1), (10,10,10))
infos = G.checkMesh(a)
print(infos)
```

(continues on next page)

(continued from previous page)

```
#> {'vmin': 1.0, 'vmax': 1.0, 'vmean': 1.0, 'vcrit': 0, 'rmin': 0.0,
↳ 'rmax': 0.0, 'rmean': 0.0, 'rcrit': 0, 'amin': 0.0, 'amax': 0.0, 'amean'
↳ ': 0.0, 'acrit': 0, 'omin': 0.0, 'omax': 0.0, 'omean': 0.0, 'ocrit': 0}
```

3.7 Operations on distributions

Generator.**enforceX**(*a*, *x0*, *enforcedh*, (*supp*, *add*))

Enforce a region around a line $x=x_0$. The size of the cell around the line is *enforcedh*. “supp” points are suppressed from the starting distribution on the left and right side. “add” points are added on the left and add points are added on the right. Add exactly add points. Adjust add in order to have a monotonic distribution with: Generator.enforceX(*a*, *x0*, *enforcedh*, *supp*, *add*). Exists also for Y and Z directions: Generator.enforceY, Generator.enforceZ.

Parameters

- **a** (array or pyTree) – input structured mesh
- **x0** (float) – X-coordinate for refinement
- **enforcedh** (float) – cell size near refinement
- **supp** (integer) – number of suppressed points
- **add** (integer) – number of added points

Returns

modified reference copy of *a*

Return type

array or pyTree

Example of use:

- Structured mesh refinement around a line $x=x_0$ (array):

```
# - enforceX (array) -
import Generator as G
import Converter as C

Ni = 50; Nj = 50
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))
# Monotonic distribution
b = G.enforceX(a, 0.3, 0.001, (13,25))
C.convertArrays2File([b], "out.plt")
```

- Structured mesh refinement around a line $x=x_0$ (pyTree):

```
# - enforceX (pyTree) -
import Generator.PyTree as G
import Converter.PyTree as C

Ni = 50; Nj = 50; Nk = 2
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,Nk))
a = G.enforceX(a, 0.3, 0.001, (13,25))
C.convertPyTree2File(a, 'out.cgns')
```

Generator.**enforceMoinsX**(a, enforcedh, (supp, add))

Same as before but with a one sided distribution (left). This can be usefull to create a boundary layer distribution in an Euler mesh. Adjust add in order to have a monotonic distribution with: Generator.enforceMoinsX(a, enforcedh, supp, add). Exists also for Y and Z directions: Generator.enforceMoinsY, Generator.enforceMoinsZ.

Parameters

- **a** (array or pyTree) – input structured mesh
- **enforcedh** (float) – cell size near refinement
- **supp** (integer) – number of suppressed points
- **add** (integer) – number of added points

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Structured mesh refinement at left side (array):

```
# - enforceMoinsX (array) -
import Generator as G
import Converter as C

Ni = 50; Nj = 50
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))
b = G.enforceMoinsX(a, 1.e-3, (10,15))
C.convertArrays2File([b], "out.plt")
```

- Structured mesh refinement at left side (pyTree):

```
# - enforceMoinsX (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G

Ni = 50; Nj = 50; Nk = 1
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,Nk))
b = G.enforceMoinsX(a, 1.e-3, (10,15))
C.convertPyTree2File(b, 'out.cgns')
```

Generator.**enforcePlusX**(a, enforcedh, (supp, add))

Same as before but with a one sided distribution (right). Adjust add in order to have a monotonic distribution with: Generator.enforcePlusX(a, x0, enforcedh, supp, add). Exists also for Y and Z directions: Generator.enforceMoinsY, Generator.enforcePlusZ.

Parameters

- **a** (array or pyTree) – input structured mesh
- **enforcedh** (float) – cell size near refinement
- **supp** (integer) – number of suppressed points
- **add** (integer) – number of added points

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Structured mesh refinement at right side (array):

```
# - enforcePlusX (array) -
import Generator as G
import Converter as C

# Distribution
Ni = 50; Nj = 50
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))
b = G.enforcePlusX(a, 1.e-3, (10,20))
C.convertArrays2File([b], "out.plt")
```

- Structured mesh refinement at right side (pyTree):

```
# - enforcePlusX (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G

# Distribution
Ni = 50; Nj = 50
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))
b = G.enforcePlusX(a, 1.e-3, (10,20))
C.convertPyTree2File(b, 'out.cgns')
```

Generator.**enforceLine**(*a*, *line*, *enforcedh*, (*supp*, *add*))

Enforce a curvilinear line defined by the array *line* in a distribution defined by the array *a*.

Parameters

- **a** (array or pyTree) – input 2D distribution
- **line** (array) – line
- **enforcedh** (float) – cell size near refinement
- **supp** (integer) – number of suppressed points
- **add** (integer) – number of added points

Returns

modified reference copy of *a*

Return type

array or pyTree

Example of use:

- Distribution refinement around a line (array):

```
# - enforceLine (array) -
import Generator as G
import Converter as C
import Geom as D

Ni = 50; Nj = 50
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))
b = D.line((0.,0.2,0.), (1.,0.2,0.), 20)
c = G.enforceLine(a, b, 0.01, (5,3))
C.convertArrays2File([c], 'out.plt')
```

- Distribution refinement around a line (pyTree):

```
# - enforceLine (pyTree)-
import Generator.PyTree as G
import Converter.PyTree as C
import Geom.PyTree as D

Ni = 50; Nj = 50
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))
b = D.line((0.,0.2,0.), (1.,0.2,0.), 20)
a = G.enforceLine(a, b, 0.01, (5,3))
C.convertPyTree2File(a, 'out.cgns')
```

`Generator.enforcePoint(a, x0)`

Enforce a point in the distribution. The index of enforced point is returned.

Parameters

- **a** (array or pyTree) – input 2D distribution
- **x0** (float) – I-location of the refinement point

Returns

index of enforced point

Return type

integer

Returns

modified reference copy of a

Return type

array or pyTree

Example of use:

- Distribution refinement at a point (array):

```
# - enforcePoint (array) -
import Converter as C
import Generator as G

# distribution
Ni = 20; Nj = 20
a = G.cart((0,0,0), (1./(Ni-1),5./(Nj-1),1), (Ni,Nj,1))
b = G.enforcePoint(a, 0.5)
C.convertArrays2File([b], "out.plt")
```

- Distribution refinement at a point (pyTree):

```
# - enforcePoint (pyTree) -
import Converter.PyTree as C
import Generator.PyTree as G

Ni = 20; Nj = 20
a = G.cart((0,0,0), (1./(Ni-1),5./(Nj-1),1), (Ni,Nj,1))
b = G.enforcePoint(a, 0.5)
C.convertPyTree2File(b, 'out.cgns')
```

Generator.**enforceCurvature**(*a*, *curve*, *power=0.5*)

Enforce the curvature of an i-curve in a distribution defined by *a*. Power reflects the power of stretching.

Parameters

- **a** (array or pyTree) – input 2D distribution
- **curve** (array) – reference curve for curvature
- **power** (float) – stretching ratio

Returns

modified reference copy of *a*

Return type

array or pyTree

Example of use:

- Distribution refinement wrt. a curve curvature (array):

```
# - enforceCurvature (array) -
import Geom as D
import Generator as G
import Converter as C
import Transform as T

# Naca profile with lines
a = D.naca(12., 501)
l1 = D.getLength(a)
a2 = D.line((1.,0.,0.), (2.,0.,0.), 500)
l2 = D.getLength(a2)
b = T.join(a, a2)
c = D.line((2.,0.,0.), (1.,0.,0.), 500)
res = T.join(c, b)
```

(continues on next page)

(continued from previous page)

```
# Distribution on the profile
l = l1+2*l2
Ni = 100; Nj = 100
p1 = l2/l; p2 = (l2+l1)/l
h = (p2-p1)/(Ni-1)
distrib = G.cart((p1,0,0), (h, 0.25/Nj,1), (Ni,Nj,1))
distrib = G.enforceCurvature(distrib, res, 0.6)
C.convertArrays2File([distrib], "out.plt")
```

- Distribution refinement wrt. a curve curvature (pyTree):

```
# - enforceCurvature (pyTree) -
import Geom.PyTree as D
import Generator.PyTree as G
import Converter.PyTree as C

a = D.naca(12., 501)

# Distribution on the profile
Ni = 20; Nj = 20; Nk = 1; h = 1./(Ni-1)
b = G.cart((0,0,0), (h, 0.25/Nj,1), (Ni,Nj,Nk))
b = G.enforceCurvature(b, a, 0.6)
C.convertPyTree2File(b, 'out.cgns')
```

`Generator.addPointInDistribution(a, ind)`

Add a point in a distribution at index `ind`.

Parameters

- `a` (array or pyTree) – input distribution
- `ind` (integer) – I-index of inserted point

Returns

modified reference copy of `a`

Return type

array or pyTree

Example of use:

- Point insertion in a distribution (array):


```
# - addPointInDistribution (array) -
import Generator as G
import Converter as C

# Distribution
Ni = 50; Nj = 50
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,1))
b = G.addPointInDistribution( a, Ni )
C.convertArrays2File([b], 'out.plt')
```

- Point insertion in a distribution (pyTree):

```
# - addPointInDistribution (pyTree)-
import Generator.PyTree as G
import Converter.PyTree as C

# Distribution
Ni = 50; Nj = 50
a = G.cart((0,0,0), (1./(Ni-1), 0.5/(Nj-1),1), (Ni,Nj,2))
b = G.addPointInDistribution(a, Ni)
C.convertPyTree2File(b, 'out.cgns')
```

CHAPTER
FOUR

INDEX

- genindex
- modindex
- search